

Data sheet | Item number: 214-187

Capacitor terminal block; with guiding collar; Protection class II without discharge resistor; PUSH WIRE® connection; 1,50 mm²; white

www.wago.com/214-187



Data

Connection data

Connection technology	PUSH WIRE®
Strip length	7 ... 8 mm / 0.28 ... 0.31 inch
Total number of connection points	4
Total number of potentials	2
Number of connection types	1

Material Data

Color	white
Weight	2.7 g

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

Commercial data

Product Group	8 (Misc. Chassis Mount Blocks)
Packaging type	BOX
Country of origin	CH
GTIN	4044918296656
Customs Tariff No.	85369010000

Electrical data

Ratings per IEC/EN 60664-1


Rated voltage (III / 2)	500 V
Rated impulse voltage (III / 2)	4 kV
Rated voltage (II / 2)	250 V
Rated current	2 A
Legend (ratings)	(III / 2) \triangleq Overvoltage category III / Pollution degree 2

Approvals per UL 1059

Approvals per	UL 1059
---------------	---------

Approvals / Certificates

UL-Approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL UL International Germany GmbH	UL 1059	20160630-E45172

Counterpart

Downloads

Documentation

Additional Information

Technical explanations	Apr 3, 2019	pdf 3.6 MB	Download
------------------------	-------------	---------------	----------

Subject to changes. Please also observe the further product documentation!



Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.