

**Data sheet | Item number: 214-251**

Capacitor cover; with integrated terminals; with discharge resistor 1.2 MO/0.33 W; PUSH WIRE® connection; 1,50 mm<sup>2</sup>



[www.wago.com/214-251](http://www.wago.com/214-251)



**Data**

**Electrical data**

**IEC Approvals**

Rated voltage (III/2)	500 V
Rated surge voltage (III/2)	4 kV
Rated current	2 A

**Connection data**

Connection technology

Subject to changes. Please also observe the further product documentation!

WAGO Corporation  
Germantown, WI 53022  
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222  
Email: [info.us@wago.com](mailto:info.us@wago.com) | Web: [www.wago.us](http://www.wago.us)

Do you have any questions about our products?  
We are always happy to take your call at {0}.



	PUSH WIRE®
Strip length	7 ... 8 mm / 0.28 ... 0.31 inch
Total number of connection points	2
Total number of potentials	2

### Material data


Fire load	0.099 MJ
Weight	4.3 g

### Commercial data

Product Group	8 (Misc. Chassis Mount Blocks)
Packaging type	BOX
GTIN	4044918756587

### Approvals / Certificates

#### UL-Approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL UL International Germany GmbH	UL 1059	20160630- E45172

### Downloads

#### Documentation

#### Additional Information

Technical explanations	2019 Apr 3	pdf 2.0 MB	Download
------------------------	------------	---------------	----------

### Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Corporation  
Germantown, WI 53022  
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222  
Email: [info.us@wago.com](mailto:info.us@wago.com) | Web: [www.wago.us](http://www.wago.us)

Do you have any questions about our products?  
We are always happy to take your call at {0}.