This item has been discontinued and as of 08.05.2017, can no longer be delivered.



Data sheet | Item number: 258-298 Thermal transfer printer www.wago.com/258-298





| lem No. | Width | Ink Ribbon | Marking Accessories | | Printer |
|----------|--------|------------|--------------------------------------------------------------------------------------|---------------------|-----------|
| 258 43 | 60 mm | resin/wax | Lobals (poper) | | all types |
| 258 44 | 100 mm | resin/wax | Labels (paper) for cable morking 211-155 / 211-156 | | all types |
| 258-145 | 38 mm | resin | 2009 Seves marking strip 709 Series marking strip | 2009-xxx 709-xxx | TP 343 |
| 258-149 | 50 mm | resin | Marking Strip Series 2009 Marking Strip Series 709 | 2009-жжж 709 кжк | FP 298+ |
| 258150 | 7á mm | resin | Marking cards for wire marking 211-111 and 211-121 Labeis (polyester) up to 76 mm | | all types |
| 258157 | 100 mm | resin | Kabels (polyaster) up in 100 mr | n . | oli types |

Data

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG Hansastr. 27 32423 Minden Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

Data sheet | Item number: 258-298 www.wago.com/258-298 System Requirements



RAM memory

8 MB RAM

Technical Data

| Printing method | Thermal/thermal transfer |
|--------------------------------------|-------------------------------------------------------------------------------------------|
| Print head | Thick-film |
| Print resolution | 300 dpi |
| Print speed | 100 mm/sec. |
| Print width | 108.4 mm |
| See-through/reflective sensor | standard |
| Processor 32 Bit ColdFire/clock rate | 64 MHz |
| Program memory | 4 MB Flash |
| Slot for memory card | CompactFlash Type 1 |
| Interfaces | ETHERNET 10/100 Base T, RS-232 (COM), USB |
| Accessories (optional) | Cutter, external unwinder, external rewinder, memory card Compact Flash Type 16-512 MB |
| Operating voltage | 100 240 VAC / 50 60 Hz, PFC |
| Safety approvals | CE, FCC class 1 |

Geometrical Data

| Height | 274 mm / 10.787 inch |
|--------|----------------------|
| Width | 242 mm / 9.528 inch |
| Depth | 446 mm / 17.559 inch |

Material Data

| Weight | 10000 g |
|--------|---------|
| | |

Environmental Requirements

| Surrounding air (operating) temperature | 10 35 °C | |
|-----------------------------------------|----------|--|
|-----------------------------------------|----------|--|

Commercial data

| Product Group | 14 (Tools) |
|--------------------|---------------|
| Packaging type | BOX |
| Country of origin | DE |
| GTIN | 4045454329211 |
| Customs Tariff No. | 84433210000 |

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KGDo you have any questions about our products?Hansastr. 27We are always happy to take your call at +49 (571) 887-44222.32423 MindenPhone: +49571 887-0 | Fax: +49571 887-169Email: info.de@wago.com | Web: www.wago.comEmail: info.de@wago.com | Web: www.wago.com

This item has been discontinued and as of 08.05.2017, can no longer be delivered.





Data sheet | Item number: 258-298 www.wago.com/258-298

Counterpart

| Downloads Device Files | | |
|---------------------------|---------------|----------|
| Device Driver | | |
| Schulung | pdf 6.8 MB | Download |

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG Hansastr. 27 32423 Minden Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.