

## Data sheet | Item number: 706-100/515-300

Connection cable; 15-pole; with solder pin; Male connector; open-ended;  
Length: 3 m; Conductor cross-section: 0.25 mm<sup>2</sup>



[www.wago.com/706-100\\_515-300](http://www.wago.com/706-100_515-300)

### Item description

#### Note:

When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

### Data

#### Electrical data

Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

#### Connection data

Number of poles	15
Connection type (1)	System
Pole number 1	15
Pluggable connectors	D-sub male connector
Connection type 2	Open-ended
Cable type	LiYCY
Wire cross-section	0.25 mm <sup>2</sup>
Color code	per DIN VDE 47100

#### Physical data

Cable length	3 m
--------------	-----

#### Material data

Weight	335 g
--------	-------

#### Environmental requirements

Surrounding air temperature (operation)	-20 ... 50 °C
---	---------------

Subject to changes. Please also observe the further product documentation!

WAGO Corporation  
Germantown, WI 53022  
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222  
Email: [info.us@wago.com](mailto:info.us@wago.com) | Web: [www.wago.us](http://www.wago.us)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



### Commercial data

PU (SPU)	1 Stück
Packaging type	box
Country of origin	FR
GTIN	4050821835455
Customs tariff number	85444290900

### Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Corporation  
Germantown, WI 53022  
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222  
Email: [info.us@wago.com](mailto:info.us@wago.com) | Web: [www.wago.us](http://www.wago.us)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.