

Data sheet | Item number: 706-160/550-200

Connection cable; 50-pole; with solder pin; Male and female connector; 50-pole; D-subminiature; Length: 2 m; Conductor cross-section: 0.25 mm²

www.wago.com/706-160_550-200



Item description

Note:

When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Data

Electrical data

Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Connection data

Number of poles	50
Connection type (1)	System
Pole number 1	50
Pluggable connectors	D-sub male connector
Connection type 2	System
Pole number 2	50
Connector 2	Sub-Min-D; female connector
Cable type	LiYCY
Wire cross-section	0.25 mm ²
Color code	per DIN VDE 47100

Physical data

Cable length	2 m
--------------	-----

Material data

Weight	1.1 g
--------	-------

Environmental requirements

Surrounding air temperature (operation)	-20 ... 50 °C
-----------------------------------------	---------------

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Commercial data

PU (SPU)	1 Stück
Packaging type	box
Country of origin	FR
GTIN	4050821836001
Customs tariff number	85444290900

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.