

## Data sheet | Item number: 706-2500/304-200

System cable; for Siemens S7-1500; 16 digital inputs or outputs (compact);  
Length: 2 m; Conductor cross-section: 0.14 mm<sup>2</sup>



[www.wago.com/706-2500\\_304-200](http://www.wago.com/706-2500_304-200)



### Data

#### Notes

Note When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.

#### Electrical data

Inputs/outputs	2 x 16 digital inputs or outputs
Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	1 A

#### Connection data

Compatible PLC Modules	Siemens S7-1500
Compatible PLC I/O Card Types	6ES7 521-1BH10-0AA0 6ES7 522-1BH10-0AA0
Connection type (1)	System
Pole number 1	20
Pluggable connectors	Pluggable connector per DIN 41651; Female connector
Connection type 2	System
Pole number 2	40
Connector 2	Siemens 6ES7-592-1BM00-0XB0
Cable type	LiYY

Subject to changes. Please also observe the further product documentation!

WAGO Corporation  
Germantown, WI 53022  
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222  
Email: [info.us@wago.com](mailto:info.us@wago.com) | Web: [www.wago.us](http://www.wago.us)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



Wire cross-section	0.14 mm <sup>2</sup>
Color code	per DIN VDE 47100

**Physical data**

Cable length	2 m
--------------	-----

**Material data**

Weight	24 g
--------	------

**Environmental requirements**

Surrounding air temperature (operation)	-20 ... 50 °C
---	---------------

**Commercial data**

PU (SPU)	1 Stück
Packaging type	bag
Country of origin	FR
GTIN	4055143456401
Customs tariff number	85444290900

**Downloads****Documentation****System Description**

WAGO System Wiring, Selection Guide	pdf	Download
This guide will help you select the appropriate interface modules and system cables for the controller you are using.	545.9 kB	

**Environmental Product Compliance****Compliance Search**

Environmental Product Compliance 706-2500/304-200	URL	Download
System cable; for Siemens S7-1500; 16 digital inputs or outputs (compact); Length: 2 m; Conductor cross-section: 0.14 mm <sup>2</sup>		

**Installation Notes**

Subject to changes. Please also observe the further product documentation!

WAGO Corporation  
 Germantown, WI 53022  
 Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222  
 Email: [info.us@wago.com](mailto:info.us@wago.com) | Web: [www.wago.us](http://www.wago.us)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.