



### Item description

The WAGO Communication Cable provides a simple option for communication with WAGO software tools (WAGO-I/O-CHECK, WAGO-I/O-PRO, ...).

**Notice:** The communication cable shall not be connected or removed when energized.

### Data

#### Technical Data

Connection type	4-pole male connector - Buchse D-Sub 9
No. of poles	4
Cable length	2.5 m

#### Geometrical Data

Width	15 mm / 0.591 inch
Height	50 mm / 1.97 inch
Depth	19 mm / 0.748 inch

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Mechanical data

Weight	79.2 g
Color	black

## Environmental Requirements

Surrounding air (operating) temperature	0 ... 55 °C
Protection class	IP20

## Commercial data

Product Group	15 (Remote I/O)
Packaging type	BOX
Country of origin	DE
GTIN	4045454394301
Customs Tariff No.	85444290900

## Counterpart

### Downloads

#### Documentation

##### Bid Text

750-920 doc - Datei	Jan 13, 2016	doc 23.6 kB	Download
750-920 GAEB X81 - Datei	Feb 19, 2019	xml 3.3 kB	Download

#### System Description

750/753 Series I/O-System – General Product Information	pdf 1.7 MB	Download
---	---------------	----------

### CAD/CAE-Data

#### CAE data

WSCAD Universe 750-920	URL	Download
------------------------	-----	----------

Subject to changes. Please also observe the further product documentation!



## Installation Notes

Subject to changes. Please also observe the further product documentation!

---

WAGO Kontakttechnik GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.