




Basic relay; Nominal input voltage: 24 VDC; 2 changeover contacts

www.wago.com/788-185





 $\label{lem:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$


WAGO Kontakttechnik GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.





www.wago.com/788-185



Data

Technical Data

Control circuit

Nominal input voltage U _N	DC 24 V
Nominal input current at U _N	0

Load circuit:

Number of changeover/switchover contacts	2
Contact material (relay)	AgCdO
Limiting continuous current	8 A
Max. switching voltage	AC 250 V
Max. switching power (resistive)	AC 2000 VA
Pull-in time (typ.)	9 ms
Drop-out time (typ.)	3 ms

Safety and protection:

Dielectric strength, control/load circuit (AC, 1 min)	5 kVrms
Dielectric strength open contact (AC, 1 min)	1 kVrms
Dielectric strength, load/load circuit (AC, 1 min)	2.5 kVrms
Protection class	IP40

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO Kontakttechnik GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.





www.wago.com/788-185

Geometrical Data

Width	12.7 mm / 0.5 inch
Height from the surface	25.5 mm / 1.004 inch
Depth	29 mm / 1.142 inch

Mechanical data

Type of mounting	Pluggable module
Type of filouridia	Fluddable Hoddle

Material Data

Fire load	0.263 MJ
Weight	17 g

Environmental Requirements

Surrounding air (operating) temperature at U_N	-40 85 °C
Surrounding air (storage) temperature	-40 85 °C

Standards and specifications

Standards/specifications	EN 61810-1
--------------------------	------------

Commercial data

Product Group	6 (Interface Electronics)
Packaging type	BOX
Country of origin	CZ
GTIN	4050821868095
Customs Tariff No.	85364900990

Counterpart

Downloads

Documentation

Additional Information

Disposal; Electrical and electronic equipment, Packaging	V 1.0.0	pdf	Download
		265.8 kB	

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO Kontakttechnik GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.





www.wago.com/788-185

CAD/CAE-Data

CAE data

WSCAD Universe 788-185 URL Download

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.