


Data sheet | Item number: 834-1203

Male connector; 100% protected against mismatching; Pin spacing 17.5 mm / 0.689 in; 3-pole; 35,00 mm²; light gray

www.wago.com/834-1203



Data

Electrical data

Ratings per IEC/EN 60664-1

Rated voltage (III / 3)	1000 V
Rated impulse voltage (III / 3)	8 kV
Rated current	125 A
Legend (ratings)	(III / 3) ≙ Overvoltage category III / Pollution degree 3

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Connection data

Solid conductor	6 ... 35 mm ² / 8 ... 2 AWG
Fine-stranded conductor	6 ... 35 mm ² / 8 ... 2 AWG
Strip length	25 mm / 0.98 inch
No. of poles	3
Total number of connection points	3
Total number of potentials	3
Type of wiring	Side-entry wiring

Geometrical Data

Pin spacing	17.5 mm / 0.689 inch
Width	68.5 mm / 2.697 inch
Height	60 mm / 2.362 inch
Depth	68.2 mm / 2.685 inch

Plug connection

Contact type (pluggable connector)	Male connector/plug
------------------------------------	---------------------

Material Data

Color	light gray
Insulating material	Polyamide 66 (PA 66)
Fire load	3.011 MJ
Weight	190 g

Commercial data

Product Group	3 (Multi Conn. System)
Packaging type	Karton
Country of origin	DE
GTIN	4045454753856
Customs Tariff No.	85366990990

Approvals / Certificates

Country specific Approvals

Logo	Approval	Additional Approval Text	Certificate name
------	----------	--------------------------	------------------

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



CCA
DEKRA Certification B.V.

EN 61984

2135360.01





CCA
DEKRA Certification B.V.

EN 61984

NTR NL
6761

UL-Approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL UL International Germany GmbH	-	E45172
	UL UL International Germany GmbH	UL 1059	20190731- E45172

Counterpart

Downloads

CAD/CAE-Data

CAD data

2D/3D Models 834-1203	URL	Download

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.