

Data sheet | Item number: 2050-391

End plate; for terminal blocks with snap-in mounting foot; 3.4 mm thick; gray

www.wago.com/2050-391



Data

Physical data

Width	3.4 mm / 0.134 inch
Height	32.1 mm / 1.264 inch
Depth	25.2 mm / 0.992 inch

Material data

Color	gray
Flammability class per UL94	V0
Fire load	0.036 MJ
Weight	1.2 g

Commercial data

PU (SPU)	100 (25) Stück
Packaging type	box

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Country of origin	DE
GTIN	4055143951340
Customs tariff number	8538906000

Downloads**Documentation****Additional Information**

Technical explanations	2019 Apr 3	pdf 2.2 MB	Download
------------------------	------------	---------------	----------

CAD files**CAD data**

2D/3D Models 2050-391	URL	Download
-----------------------	-----	----------

CAE data

ZUKEN Portal 2050-391	URL	Download
-----------------------	-----	----------

EPLAN Data Portal 2050-391	URL	Download
----------------------------	-----	----------

	URL	Download
--	-----	----------

Environmental Product Compliance**Compliance Search**

Environmental Product Compliance 2050-391	URL	Download
End plate; for terminal blocks with snap-in mounting foot; 3.4 mm thick; gray		

Installation Notes**Product family****TOPJOB® S**

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
 Germantown, WI 53022
 Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
 Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.