# Data sheet | Item number: 280-762

Terminal block for pluggable modules; 4-pole; with 4-conductor terminal blocks; with marker carrier; with orange separator; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm²; CAGE CLAMP®; 2,50 mm²; gray

www.wago.com/280-762

RoHS ✓ Compliant

BOMcheck.net

Color:

## Data

### Electrical data

| | |
|---|---|
| Rated continuous current | 10 A |

### Safety and protection:

| | |
|---|---|
| Rated voltage | 400 V |
| Rated impulse voltage | 6 kV |
| Pollution degree | 3 |

### Connection data

| | |
|---|---|
| Total number of potentials | 2 |
| Number of connection types | 4 |
| Connection technology | CAGE CLAMP® |
| Solid conductor | 0.08 … 2.5 mm² / 28 … 14 AWG |
| Fine-stranded conductor | 0.08 … 2.5 mm² / 28 … 14 AWG |
| Strip length | 8 … 9 mm / 0.31 … 0.35 inch |

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

| | |
|---|---|
| Type of wiring | Front-entry wiring |

## Geometrical Data

| | |
|---|---|
| Width | 15 mm / 0.591 inch |
| Height from upper-edge of DIN-35 rail | 28 mm / 1.102 inch |
| Depth | 73 mm / 2.874 inch |

## Mechanical data

| | |
|---|---|
| Type of mounting | DIN-35 rail |

## Material Data

| | |
|---|---|
| Color | gray |
| Fire load | 0.386 MJ |
| Weight | 20 g |

## Commercial data

| | |
|---|---|
| Packaging type | BOX |
| Country of origin | DE |
| GTIN | 4044918635653 |
| Customs Tariff No. | 85369010000 |

## Counterpart

## Compatible products

**tools**

| | | |
|---|---|---|
| | **Item no.: 210-657**<br>Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; short | www.wago.com/210-657 |
| | **Item no.: 210-658**<br>Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft; angled; short | www.wago.com/210-658 |

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

| | | |
|---|---|---|
| | **Item no.: 210-720**<br>Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft | www.wago.com/210-720 |

**Jumper**

| | | |
|---|---|---|
| | **Item no.: 210-103**<br>Wire commoning chain; insulated; 50 connections; black | www.wago.com/210-103 |
|  | **Item no.: 210-123**<br>Wire commoning chain; insulated; 50 connections | www.wago.com/210-123 |
| | **Item no.: 280-482**<br>Comb-style jumper bar; insulated; 2-way; IN = IN terminal block; gray | www.wago.com/280-482 |
| | **Item no.: 280-483**<br>Comb-style jumper bar; insulated; 3-way; IN = IN terminal block; gray | www.wago.com/280-483 |
| | **Item no.: 280-484**<br>Comb-style jumper bar; insulated; 4-way; IN = IN terminal block; gray | www.wago.com/280-484 |
| | **Item no.: 280-485**<br>Comb-style jumper bar; insulated; 5-way; IN = IN terminal block; gray | www.wago.com/280-485 |
| | **Item no.: 280-490**<br>Comb-style jumper bar; insulated; 10-way; IN = IN terminal block; gray | www.wago.com/280-490 |
| | **Item no.: 280-492**<br>Alternate comb-style jumper bar; insulated; 2-way; IN = IN terminal block; gray | www.wago.com/280-492 |
| | **Item no.: 709-110**<br>Wire commoning chain; insulated; 4 connections; 3 x 110 mm; black | www.wago.com/709-110 |
| | **Item no.: 709-111**<br>Wire commoning chain; insulated; 3 connections; 2 x 120 mm; black | www.wago.com/709-111 |
| | **Item no.: 709-112**<br>Wire commoning chain; insulated; 3 connections; 2 x 170 mm; black | www.wago.com/709-112 |

**ferrule**

| | | |
|---|---|---|
| | **Item no.: 216-101**<br>Ferrule; Sleeve for 0.5 mm² / AWG 22; uninsulated; electro-tin plated | www.wago.com/216-101 |
| | **Item no.: 216-102**<br>Ferrule; Sleeve for 0.75 mm² / AWG 20; uninsulated; electro-tin plated | www.wago.com/216-102 |
| | **Item no.: 216-103**<br>Ferrule; Sleeve for 1 mm² / AWG 18; uninsulated; electro-tin plated | www.wago.com/216-103 |
| | **Item no.: 216-104**<br>Ferrule; Sleeve for 1.5 mm² / AWG 16; uninsulated; electro-tin plated | www.wago.com/216-104 |
| | **Item no.: 216-201**<br>Ferrule; Sleeve for 0.5 mm² / 20 AWG; insulated; electro-tin plated; white | www.wago.com/216-201 |
| | **Item no.: 216-202** | |

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

| | | |
|---|---|---|
| | Ferrule; Sleeve for 0.75 mm² / 18 AWG; insulated; electro-tin plated; gray | www.wago.com/216-202 |
| | **Item no.: 216-203**<br>Ferrule; Sleeve for 1 mm² / AWG 18; insulated; electro-tin plated; red | www.wago.com/216-203 |
| | **Item no.: 216-204**<br>Ferrule; Sleeve for 1.5 mm² / AWG 16; insulated; electro-tin plated; black | www.wago.com/216-204 |
| | **Item no.: 216-301**<br>Ferrule; Sleeve for 0.25 mm² / AWG 24; insulated; electro-tin plated; yellow | www.wago.com/216-301 |
| | **Item no.: 216-302**<br>Ferrule; Sleeve for 0.34 mm² / 22 AWG; insulated; electro-tin plated; green | www.wago.com/216-302 |
| **General accessories** | | |
| | **Item no.: 231-668**<br>Lockout caps; for covering unused clamping units; gray | www.wago.com/231-668 |
| | **Item no.: 231-669**<br>Lockout caps; for covering unused clamping units; orange | www.wago.com/231-669 |
| | **Item no.: 286-110**<br>Empty component plug housing; Type 9; 10 mm wide; 4-pole; gray | www.wago.com/286-110 |
| | **Item no.: 286-111**<br>Empty component plug housing; Type 10; 15 mm wide; 6-pole; gray | www.wago.com/286-111 |
| | **Item no.: 286-112**<br>Empty component plug housing; Type 11; 20 mm wide; 8-pole; gray | www.wago.com/286-112 |
| | **Item no.: 286-113**<br>Empty component plug housing; Type 12; 25 mm wide; 10-pole; gray | www.wago.com/286-113 |
| | **Item no.: 286-304**<br>Relay module; Nominal input voltage: 24 VDC; 1 changeover contact; Limiting continuous current: 7 A; Red status indicator; Module width: 15 mm; gray | www.wago.com/286-304 |
| | **Item no.: 286-304/004-000**<br>Relay module; Nominal input voltage: 24 VDC; 1 changeover contact; Limiting continuous current: 7 A; Path; Red status indicator; Module width: 15 mm; gray | www.wago.com/286-304/004-000 |
| | **Item no.: 286-307/004-000**<br>Relay module; Nominal input voltage: 110 VDC; 1 changeover contact; Limiting continuous current: 7 A; Path; Red status indicator; Module width: 15 mm; gray | www.wago.com/286-307/004-000 |
| | **Item no.: 286-312**<br>Relay module; Relay with 2 changeover contacts (2u); gray | www.wago.com/286-312 |
| | **Item no.: 286-312/004-000**<br>Relay module; Nominal input voltage: 24 VDC; 2 changeover contacts; Limiting continuous current: 5 A; Path; Red status indicator; Module width: 20 mm; gray | www.wago.com/286-312/004-000 |
| | **Item no.: 286-316** | |

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

| | | |
|---|---|---|
| | Relay module; Nominal input voltage: 220 VDC; 2 changeover contacts; Limiting continuous current: 7 A; Red status indicator; Module width: 20 mm; gray | www.wago.com/286-316 |
| | **Item no.: 286-320**<br>Relay module; Nominal input voltage: 24 VDC; 1 break and 1 make contact; Limiting continuous current: 6 A; Red status indicator; Module width: 20 mm; gray | www.wago.com/286-320 |
| | **Item no.: 286-320/004-000**<br>Relay module; Nominal input voltage: 24 VDC; 1 break and 1 make contact; Path; Red status indicator; Module width: 20 mm; gray | www.wago.com/286-320/004-000 |
| | **Item no.: 286-328**<br>Relay module; Nominal input voltage: 24 VDC; 2 make contact; Limiting continuous current: 6 A; Red status indicator; Module width: 20 mm; gray | www.wago.com/286-328 |
| | **Item no.: 286-328/004-000**<br>Relay module; Nominal input voltage: 24 VDC; 2 make contact; Limiting continuous current: 6 A; Path; Red status indicator; Module width: 20 mm; gray | www.wago.com/286-328/004-000 |
| | **Item no.: 286-336/001-000**<br>Relay module; Nominal input voltage: 24 VDC; 2 break and 2 make contacts; Red status indicator; Module width: 25 mm; gray | www.wago.com/286-336/001-000 |
| | **Item no.: 286-344/004-000**<br>Relay module; Nominal input voltage: 24 VDC; 3 break contacts and 1 make contact; Path; Red status indicator; Module width: 25 mm; gray | www.wago.com/286-344/004-000 |
| | **Item no.: 286-352/004-000**<br>Relay module; Nominal input voltage: 24 VDC; 4 make contacts; Limiting continuous current: 5 A; Path; Red status indicator; Module width: 25 mm; gray | www.wago.com/286-352/004-000 |
| | **Item no.: 286-364**<br>Relay module; Nominal input voltage: 24 VDC; 1 make contact; Limiting continuous current: 5 A; Red status indicator; Module width: 10 mm; gray | www.wago.com/286-364 |
| | **Item no.: 286-364/004-000**<br>Relay module; Nominal input voltage: 24 VDC; 1 make contact; Path; Red status indicator; Module width: 10 mm; gray | www.wago.com/286-364/004-000 |
| | **Item no.: 286-368**<br>Relay module; Nominal input voltage: 24 VDC; 1 break contact; Limiting continuous current: 5 A; Red status indicator; Module width: 10 mm; gray | www.wago.com/286-368 |
| | **Item no.: 286-368/004-000**<br>Relay module; Nominal input voltage: 24 VDC; 1 break contact; Path; Red status indicator; Module width: 10 mm | www.wago.com/286-368/004-000 |
| | **Item no.: 286-376**<br>Relay module; Nominal input voltage: 24 VDC; 1 make contact; Limiting continuous current: 5 A; for switching higher DC loads; Red status indicator; Module width: 15 mm; gray | www.wago.com/286-376 |
| | **Item no.: 286-380**<br>Bistable relay module; Nominal input voltage: 24 VDC; 1 changeover contact; Limiting continuous current: 6 A; Red status indicator; Module width: 15 mm; gray | www.wago.com/286-380 |
| | **Item no.: 286-381**<br>Bistable relay module; Nominal input voltage: 24 VDC; 1 changeover contact; Limiting continuous | www.wago.com/286-381 |

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

| | | |
|---|---|---|
| | current: 6 A; Red status indicator; Module width: 15 mm; gray | |
| | **Item no.: 286-394/004-000**<br>Relay module; Nominal input voltage: 24 VDC; 1 changeover contact; Path; Red status indicator; Module width: 15 mm; light gray | www.wago.com/286-394/004-000 |
| | **Item no.: 286-427**<br>Timer relay module; Nominal input voltage: 24 VDC; Limiting continuous current: 5 A; Pulse lengthening: 1 … 10 s; Red status indicator; Module width: 20 mm; gray | www.wago.com/286-427 |
| | **Item no.: 286-507**<br>Relay module; Nominal input voltage: 115 VAC; 1 changeover contact; Limiting continuous current: 7 A; Red status indicator; Module width: 15 mm; gray | www.wago.com/286-507 |
| | **Item no.: 286-508**<br>Relay module; Nominal input voltage: 230 VAC; 1 changeover contact; Limiting continuous current: 7 A; Red status indicator; Module width: 15 mm; gray | www.wago.com/286-508 |
| | **Item no.: 286-516**<br>Relay module; Nominal input voltage: 230 VAC; 2 changeover contacts; Limiting continuous current: 7 A; Red status indicator; Module width: 15 mm; gray | www.wago.com/286-516 |
| | **Item no.: 286-573**<br>Latching relay module; Nominal input voltage: 24 VDC; 1 changeover contact; Limiting continuous current: 6 A; Red status indicator; Module width: 15 mm | www.wago.com/286-573 |
| | **Item no.: 286-575**<br>Latching relay module; Nominal input voltage: 24 VDC; 1 changeover contact; Limiting continuous current: 3 A; Path; Red status indicator; Module width: 22 mm | www.wago.com/286-575 |
| | **Item no.: 286-604/004-000**<br>Timer relay module; Nominal input voltage: 24 VDC; Limiting continuous current: 6 A; On-delay: 10 … 100 s; Red status indicator; Module width: 20 mm; gray | www.wago.com/286-604/004-000 |
| | **Item no.: 286-640**<br>Timer relay module; Nominal input voltage: 24 VDC; Limiting continuous current: 6 A; Path; Multifunction/Multitime; Yellow status indicator; Module width: 6 mm; gray | www.wago.com/286-640 |
| | **Item no.: 286-640/004-000**<br>Multifunction timing relay module; Relay with 1 changeover contact (1u); 4 time ranges; for railway operations; 4 functions; gray | www.wago.com/286-640/004-000 |
| | **Item no.: 286-661**<br>Current flow monitoring module; AC currents; adjustable; light gray | www.wago.com/286-661 |
| | **Item no.: 286-662**<br>Current flow monitoring module; DC currents; Monitoring range: 0.4 A – 3.5 A; 1 make contact; light gray | www.wago.com/286-662 |
| | **Item no.: 286-664**<br>Current flow monitoring module; AC currents; Monitoring range: 1 A – 10 A; 1 changeover contact; light gray | www.wago.com/286-664 |
| | **Item no.: 286-665**<br>Current flow monitoring module; AC currents; Monitoring range: 1 A – 10 A; 1 changeover contact; light gray | www.wago.com/286-665 |
| | **Item no.: 286-721**<br>Optocoupler module; Nominal input voltage: 24 VDC; Output voltage range: 15 … 30 VDC; Limiting | |



WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

| | | |
|---|---|---|
| | continuous current: 5 A; 3-wire connection/low-side switching; Red status indicator; Module width: 15 mm; gray | www.wago.com/286-721 |
| | **Item no.: 286-723**<br>Optocoupler module; Nominal input voltage: 24 VDC; Output voltage range: 15 … 30 VDC; Limiting continuous current: 4 A; 3-wire connection/high-side switching; Red status indicator; Module width: 15 mm; gray | www.wago.com/286-723 |
| | **Item no.: 286-725**<br>Optocoupler module; Input AC/DC 10 V ... 30 V; Output DC 24 V/ 1 mA ... 0.5 A; negative switching; gray | www.wago.com/286-725 |
| | **Item no.: 286-742**<br>S0 interface power supply; Input voltage: 230 VAC; S0 interface | www.wago.com/286-742 |
| | **Item no.: 286-752**<br>Optocoupler module; Nominal input voltage: 24 VDC; Output voltage range: 20 … 30 VDC; Limiting continuous current: 0.5 A; 3-wire connection/high-side switching; Frequency: 25 kHz; Red status indicator; Module width: 15 mm; gray | www.wago.com/286-752 |
| | **Item no.: 286-752/002-000**<br>Optocoupler module; Red status indicator; gray | www.wago.com/286-752<br>/002-000 |
| | **Item no.: 286-790**<br>Optocoupler module; gray | www.wago.com/286-790 |
| | **Item no.: 286-791**<br>Optocoupler module; Nominal input voltage: 24 VDC; Output voltage range: 20 … 60 VDC; Limiting continuous current: 0.1 A; 2-wire connection; Frequency: 3 kHz; Red status indicator; Module width: 10 mm; gray | www.wago.com/286-791 |
| | **Item no.: 286-792**<br>Optocoupler module; Red status indicator; gray | www.wago.com/286-792 |
| | **Item no.: 286-794**<br>Optocoupler module; Nominal input voltage: 24 VDC; Output voltage range: 20 … 60 VDC; Limiting continuous current: 0.1 A; 2-wire connection; Red status indicator; Module width: 10 mm; gray | www.wago.com/286-794 |
| | **Item no.: 286-797**<br>Optocoupler module; Red status indicator | www.wago.com/286-797 |
| | **Item no.: 286-803**<br>Component module with diode; gray | www.wago.com/286-803 |
| | **Item no.: 286-805**<br>Component module with diode; light gray | www.wago.com/286-805 |
| | **Item no.: 286-807**<br>Component module with diode; with 7 pcs; Diode 1N4007; with common anode; light gray | www.wago.com/286-807 |
| | **Item no.: 286-809**<br>Component module with diode; light gray | www.wago.com/286-809 |
| | **Item no.: 286-822**<br>Component module with LED; Red LED; with common cathode | www.wago.com/286-822 |

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

| | | |
|---|---|---|
| | **Item no.: 286-826**<br>AND gate module with 6 inputs; light gray | www.wago.com/286-826 |
| | **Item no.: 286-830**<br>Bridge rectifier module; Input voltage: 24 VAC; with varistor protective circuit; gray | www.wago.com/286-830 |
| | **Item no.: 286-831**<br>Surge suppression module for signal technology; Nominal voltage: 24 VAC/DC; for 2 signal paths with common surge arrester; plugged on rail-mount terminal block, 15 mm wide; gray | www.wago.com/286-831 |
| | **Item no.: 286-832**<br>Surge suppression module for signal technology; Nominal voltage: 24 VAC/DC; for 2 signal paths with common surge arrester; pluggable on rail-mount terminal block, 20 mm wide; gray | www.wago.com/286-832 |
| | **Item no.: 286-833**<br>Surge suppression module for signal technology; Nominal voltage: 24 VDC; for 1 signal path; plugged on rail-mount terminal block, 15 mm wide; gray | www.wago.com/286-833 |
| | **Item no.: 286-834**<br>Surge suppression module for signal technology; Nominal voltage: 12 VDC; for 2 signal paths with common surge arrester; pluggable on rail-mount terminal block, 20 mm wide; gray | www.wago.com/286-834 |
| | **Item no.: 286-834/024-000**<br>Surge suppression module for signal technology; Nominal voltage: 24 VDC; for 2 signal paths with common surge arrester; pluggable on rail-mount terminal block, 15 mm wide; gray | www.wago.com/286-834/024-000 |
| | **Item no.: 286-835**<br>Surge suppression module for signal technology; Nominal voltage: 230 VAC; for 2 signal paths with common surge arrester; plugged on rail-mount terminal block, 15 mm wide | www.wago.com/286-835 |
| | **Item no.: 286-835/115-000**<br>Surge suppression module for signal technology; Nominal voltage: 115 VAC; for 2 signal paths with common surge arrester; plugged on rail-mount terminal block, 15 mm wide; gray | www.wago.com/286-835/115-000 |
| | **Item no.: 286-836**<br>Surge suppression module for signal technology; Nominal voltage: 24 VAC/DC; for 2 signal paths with common surge arrester; plugged on rail-mount terminal block, 15 mm wide; gray | www.wago.com/286-836 |
| | **Item no.: 286-838**<br>Surge suppression module for signal technology; Nominal voltage: 230 VAC; for 2 signal paths with common surge arrester; with visual indicator; gray | www.wago.com/286-838 |
| | **Item no.: 286-840**<br>Bridge rectifier module; Input voltage: 250 VAC; with varistor protective circuit; gray | www.wago.com/286-840 |
| | **Item no.: 286-841**<br>Surge suppression module for signal technology; Nominal voltage: 220 VDC; for 2 signal paths with common surge arrester; pluggable on rail-mount terminal block, 25 mm wide; gray | www.wago.com/286-841 |
| | **Item no.: 286-842**<br>Surge suppression module for signal technology; Nominal voltage: 230 VAC; for 2 signal paths with common surge arrester; pluggable on rail-mount terminal block, 25 mm wide; gray | www.wago.com/286-842 |
| | **Item no.: 286-843**<br>Surge suppression module for signal technology; Nominal voltage: 115 VAC; for 2 signal paths with common surge arrester; pluggable on rail-mount terminal block, 25 mm wide; gray | www.wago.com/286-843 |
| | **Item no.: 286-844**<br>Surge suppression module for signal technology; for 2 signal paths with common surge arrester; pluggable on rail-mount terminal block, 25 mm wide; gray | www.wago.com/286-844 |

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

| | | |
|---|---|---|
| | **Item no.: 286-890**<br>Component module with fuse; for (5 x 20) mm microfuse; Nominal voltage: 24 VAC/DC; gray | www.wago.com/286-890 |
| | **Item no.: 286-891**<br>Component module with fuse; for (5 x 20) mm microfuse; Nominal voltage: 230 VAC/DC; gray | www.wago.com/286-891 |
| | **Item no.: 286-895**<br>Switching module; with changeover rocker switch; Switching voltage: 250 VAC; Switching current: 6 A; gray | www.wago.com/286-895 |
| | **Item no.: 286-896**<br>Switching module; with momentary switch; Switching voltage: 250 VAC; Switching current: 6 A; gray | www.wago.com/286-896 |
| **Marking accessories** | | |
| | **Item no.: 2009-115**<br>WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white | www.wago.com/2009-115 |
| | **Item no.: 2009-115/000-002**<br>WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; yellow | www.wago.com/2009-115/000-002 |
| | **Item no.: 2009-115/000-006**<br>WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white | www.wago.com/2009-115/000-006 |
| | **Item no.: 2009-115/000-007**<br>WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; gray | www.wago.com/2009-115/000-007 |
| | **Item no.: 2009-115/000-012**<br>WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white | www.wago.com/2009-115/000-012 |
| | **Item no.: 2009-115/000-017**<br>WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white | www.wago.com/2009-115/000-017 |
| | **Item no.: 2009-115/000-023**<br>WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; green | www.wago.com/2009-115/000-023 |
| | **Item no.: 2009-115/000-024**<br>WMB-Inline; for Smart Printer; 1500 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white | www.wago.com/2009-115/000-024 |
| | **Item no.: 249-105**<br>Group marker carrier; gray | www.wago.com/249-105 |
|  | **Item no.: 793-5501**<br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; white | www.wago.com/793-5501 |
| | **Item no.: 793-5501/000-002**<br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap- | www.wago.com/793-5501/000-002 |

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

| | | |
|---|---|---|
| | on type; yellow | |
| | **Item no.: 793-5501/000-005**<br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; red | www.wago.com/793-5501/000-005 |
| | **Item no.: 793-5501/000-006**<br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; blue | www.wago.com/793-5501/000-006 |
| | **Item no.: 793-5501/000-007**<br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; gray | www.wago.com/793-5501/000-007 |
| | **Item no.: 793-5501/000-012**<br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; orange | www.wago.com/793-5501/000-012 |
| | **Item no.: 793-5501/000-017**<br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; green | www.wago.com/793-5501/000-017 |
| | **Item no.: 793-5501/000-023**<br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; light green | www.wago.com/793-5501/000-023 |
| | **Item no.: 793-5501/000-024**<br>WMB marking card; as card; for terminal block width 5 - 17.5 mm; stretchable 5 - 5.2 mm; plain; snap-on type; violet | www.wago.com/793-5501/000-024 |
| **Carrier rail** | | |
| | **Item no.: 210-112**<br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 25 mm | www.wago.com/210-112 |
| | **Item no.: 210-113**<br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; according to EN 60715 | www.wago.com/210-113 |
| | **Item no.: 210-114**<br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; similar to EN 60715 | www.wago.com/210-114 |
| | **Item no.: 210-115**<br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 18 mm | www.wago.com/210-115 |
| | **Item no.: 210-118**<br>Steel carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715 | www.wago.com/210-118 |
| | **Item no.: 210-196**<br>Aluminum carrier rail; 35 x 8.2 mm; 1.6 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored | www.wago.com/210-196 |
| | **Item no.: 210-197**<br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; similar to EN 60715 | www.wago.com/210-197 |
| | **Item no.: 210-198** | |

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

| | | |
|---|---|---|
| | Copper carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; copper-colored | www.wago.com/210-198 |
| | **Item no.: 210-504**<br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; galvanized; according to EN 60715 | www.wago.com/210-504 |
| | **Item no.: 210-505**<br>Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; galvanized; according to EN 60715 | www.wago.com/210-505 |
| | **Item no.: 210-506**<br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; galvanized; similar to EN 60715 | www.wago.com/210-506 |
| | **Item no.: 210-508**<br>Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; galvanized; similar to EN 60715 | www.wago.com/210-508 |
| **Protective Warning Marker** | | |
| | **Item no.: 280-415**<br>Protective warning marker; with high-voltage symbol, black; for 5 terminal blocks; yellow | www.wago.com/280-415 |
| **assembling** | | |
| | **Item no.: 210-148**<br>Angled support bracket; without screw | www.wago.com/210-148 |
| | **Item no.: 210-149**<br>Screw M 5 x 8; for angled support bracket | www.wago.com/210-149 |

## Downloads

### Documentation

#### Bid Text

| | | | |
|---|---|---|---|
| 280-762<br>GAEB docx - Datei | Feb 20, 2019 | docx<br>14.3 kB | Download |
| 280-762<br>GAEB X81 - Datei | Feb 19, 2019 | xml<br>2.8 kB | Download |

#### Additional Information

| | | | |
|---|---|---|---|
| Disposal; Electrical and electronic equipment, Packaging | V 1.0.0 | pdf<br>265.8 kB | Download |

## CAD/CAE-Data

#### CAD data

| | | |
|---|---|---|
| 2D/3D Models 280-762 | URL | Download |

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

### CAE data

| | | |
|---|---|---|
| EPLAN Data Portal 280-762 | URL | Download |
| WSCAD Universe 280-762 | URL | Download |

## Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.