



Item description

Integrating machines and systems into the "Internet of Things" is incredibly quick and easy with the WAGO IoT Box Energy Data. This IoT Box features power and energy measurement functionality and is ready for immediate use. It also offers all the functions required for digitalization, from signal acquisition to cloud connectivity.

The IoT Box was designed as a plug-and-play device – no hardware engineering is needed. Collected data is transferred to the desired IoT application with just a few parameter settings.

The hardware includes a controller with its own communication interface, I/O modules with analog and digital inputs/outputs, a 3-phase power measurement module and a 24 V power supply unit.

Depending on the application, additional I/O modules can be added later to adapt the system to specific requirements.

This IoT Box includes:

- Controller PFC200; 2nd Generation; 2 x ETHERNET, RS-232/-485: 750-8212
- Switched-Mode Power Supply; Classic; 1-phase; Output voltage: 24 VDC; Output current: 2 A; NEC Class 2; DC OK signal: 787-1606
- 8-Channel Digital Input; 24 VDC; 3 ms; 2-wire connection: 750-1415
- 8-Channel Digital Output; 24 VDC; 0.5 A; 2-wire connection: 750-1515
- 8-Channel Analog Input; resistance measurement; adjustable: 750-451
- 4-Channel Analog Input; voltage/current; differential input; 16 bits; diagnostics: 750-471
- 3-Phase Power Measurement; 690 VAC; 1 A: 750-495/000-002
- Rogowski Coil; Primary rated current: 4000 A; Output signal: 22.5 mV per kA; Cable length: 1.5 m; Feedthrough for measurement conductor: 70 mm: 855-9150/2000-701
- End Module: 750-600

Subject to changes. Please also observe the further product documentation!



- SD Memory Card; pSLC-NAND; 8 GB; Temperature range: -40 ... +90 °C; 758-879/000-2108
- IoT Box application (installed and licensed)
- Circuit breaker; 1-pole; C 10 A; 10 kA
- Electrical circuit breaker; 1-pole; 24 VDC; 1 ... 8 A
- Set of wall-mount lugs
- Cable grips M16; M20; M25
- Connectors (plug and socket) for power supply

Data

Technical data

Communication	ETHERNET RS-232 serial interface RS-485 interface MQTT
ETHERNET protocols	DHCP DNS FTP FTPS HTTP HTTPS SSH
Visualization	Web-Visu
Baud rate (communication/fieldbus 1)	10/100 Mbit/s
Baud rate	ETHERNET: 10/100 Mbit/s
Supply voltage	230 VAC; (L/N/PE); 50 Hz

Physical data

Width	300 mm
Height	300 mm
Depth	210 mm

Mechanical data

Weight	9236.9 g
Conformity marking	CE

Environmental requirements

Ambient temperature (operation)	0 ... +45 °C
Surrounding air temperature (storage)	-40 ... +85 °C

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Protection type	IP20
Note on protection type	IP20/IP65; (IP65 only applies when both power and LAN cables are locked)
Pollution degree (5)	I
Relative humidity (without condensation)	95 %
Mounting type	Wall-mount

Commercial data

PU (SPU)	1 Pieces
Packaging type	box
Country of origin VKOrg Germany	DE
GTIN	4055144091496

Downloads

Documentation

Manual

WAGO Applikation IoT-Box	2.1.0 2021 Jun 23	pdf 4.9 MB	Download
--------------------------	----------------------	---------------	----------

Bid Text

2854-099/000-001 docx - Datei		docx 25 B	Download
2854-099/000-001 X81 - Datei		xml 7 B	Download

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 2854-099/000-001 IoT-Box; Energy Data		URL	Download
---	--	-----	----------

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
 Germantown, WI 53022
 Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
 Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.