

Interface module; with solder pin; Female connector; 37-pole; Mating connector with solder connection; Vertical mounting; Triple-deck PCB terminal blocks; in mounting carrier; with shield connection; 2,50 mm²




www.wago.com/289-624





 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$





Data Electrical Data

Operating voltage	≤ AC 100 V; ≤ DC 125 V	
Nominal current	2 A	
Contact resistance (max.)	30 mΩ	
Specialty functions	With shield connection	

Safety and protection:

Rated voltage	100 V
Rated impulse voltage	0.8 kV
Pollution degree	2
Protection class	IP20

Connection data

Connection type (1)	System
No. of poles	37
Pluggable connector	D-subminiature; female connector
For mating connectors	With solder connection
Mating direction	Vertical
Pull relief	Stud bolts UNC 4-40

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO Kontakttechnik GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/289-624



Connection type (2)	Field
No. of poles 2	39
Design 2	PCB terminal blocks, 3-deck
Connection technology 2	CAGE CLAMP [®]
WAGO terminal 2	WAGO 737 Series
Solid conductor (2)	0.08 2.5 mm² / 28 12 AWG
Fine-stranded conductor (2)	0.08 2.5 mm² / 28 12 AWG
Strip length (2)	5 6 mm / 0.2 0.24 inch
Note (conductor cross-section)	12 AWG: THHN, THWN
Performance level	2 / 200 mating cycles
Strain relief Strain relief	Gewindebolzen UNC 4-40

Geometrical Data

Width	74 mm / 2.913 inch
Height from upper-edge of DIN-35 rail	62 mm / 2.441 inch
Depth	85 mm / 3.346 inch

Mechanical data

Type of mounting	DIN-35 rail	
Housing design	Mounting carrier	

Material Data

Contact material (pluggable connector)	Au over Ni
Weight	123.2 g

Environmental Requirements

Surrounding air (operating) temperature	-20 50 °C
Surrounding air (storage) temperature	-40 70 °C
Relative humidity	≤ 85% (non condensing)

Standards and specifications

Standards/specifications	UL 840	

Commercial data

Product Group	6 (Interface Electronics)

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG

Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/289-624



Cartificata

Packaging type	BOX
Country of origin	DE
GTIN	4045454516451
Customs Tariff No.	85369010000

Approvals / Certificates

UL-Approvals

			Certificate
Logo	Approval	Additional Approval Text	name
	UL	UL 508	E175199
-1	Underwriters Laboratories Inc. (ORDINARY		Vol.2 Sec.
c FLI us	LOCATIONS)		1

Counterpart

Compatible products

tools

1	Item no.: 210-720	www.wago.com/210-720	
	Operating tool; Blade: 3.5 x 0.5 mm; with a partially insulated shaft		
Marking a	ccessories		
/	Item no.: 709-177		
	Marking strips; on reel; 7.5 mm wide; not stretchable; plain; snap-on type; translucent	www.wago.com/709-177	
/	Item no.: 709-178	www.wago.com/709-178	
	Marking strips; on reel; 7.5 mm wide; not stretchable; plain; snap-on type; white		
	Item no.: 709-196	www.wago.com/709-196	
	Marking strips; for laser printer; translucent		
	Item no.: 709-198	www.wago.com/709-198	
	Marking strips; white		

Downloads Documentation

32423 Minden

Bid Text

289-624 Feb 6, 2015 doc Download 27.1 kB

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO Kontakttechnik GmbH & Co. KG Hansastr. 27

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/289-624



LIDI

doc - Datei

289-624 GAEB X81 - Datei	Feb 19, 2019	xml 3.8 kB	Download
Instruction Leaflet		pdf 1.3 MB	Download
Additional Information			
Disposal; Electrical and electronic equipment, Packaging	V 1.0.0	pdf 265.8 kB	Download

CAD/CAE-Data

2D/2D Madala 200 C24

CAD data

2D/3D Models 289-624	URL	Download
CAE data		

EPLAN Data Portal 289-624		Download


WSCAD Universe 289-624 URL Download

Installation Notes

Inserting a conductor



Connection of conductor - Operating tool actuation parallel to conductor entry.



Connection of conductor - Operating tool actuation perpendicular to conductor entry.

Assembly


Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG Hansastr. 27 32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/289-624







Assembly of a module on the carrier rail

Removing a module from the DIN-rail.

Subject to changes. Please also observe the further product documentation!

Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.