Data sheet | Item number: 706-100/320-300

Connection cable; 20-pole; Pluggable connector per DIN 41651; open-ended; Length: 3 m; Conductor cross-section: 0.14 mm²

www.wago.com/706-100_320-300

Item description

Note:
When using more than 10 wires, the maximum current per wire must be reduced to 0.7 A.

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

Data

Electrical data

Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	1 A

Connection data

Number of poles	20
Connection type (1)	System
Pole number 1	20
Pluggable connectors	Pluggable connector per DIN 41651; Female connector
Connection type 2	Open-ended
Cable type	LiYY
Wire cross-section	0.14 mm²
Color code	per DIN VDE 47100

Physical data

Cable length	3 m

Material data

Weight	223 g

Environmental requirements

Surrounding air temperature (operation)	-20 … 50 °C

Commercial data

PU (SPU)	1 Stück
Packaging type	box
Country of origin	FR
GTIN	4050821835240
Customs tariff number	85444290900

Downloads

Environmental Product Compliance

Compliance Search

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

URL Download

Environmental Product Compliance 706-100/320-300

Connection cable; 20-pole; Pluggable connector per DIN 41651; open-ended;
Length: 3 m; Conductor cross-section: 0.14 mm²

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.