

Data sheet | Item number: 706-100/509-300

Connection cable; 9-pole; with solder pin; Male connector; open-ended;
Length: 3 m; Conductor cross-section: 0.25 mm²

www.wago.com/706-100_509-300



Item description

Note:

When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Data

Electrical data

Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Connection data

Number of poles	9
Connection type (1)	System
Pole number 1	9
Pluggable connectors	D-sub male connector
Connection type 2	Open-ended
Cable type	LiYCY
Wire cross-section	0.25 mm ²
Color code	per DIN VDE 47100

Physical data

Cable length	3 m
--------------	-----

Material data

Weight	1500 g
--------	--------

Environmental requirements

Surrounding air temperature (operation)	-20 ... 50 °C
---	---------------

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Commercial data

PU (SPU)	1 Stück
Packaging type	bag
GTIN	4055143651660
Customs tariff number	85444290900

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-100/509-300	URL	Download
Connection cable; 9-pole; with solder pin; Male connector; open-ended; Length: 3 m; Conductor cross-section: 0.25 mm ²		

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.