Data sheet | Item number: 706-160/515-100

Connection cable; 15-pole; with solder pin; Male and female connector; 15-pole; D-subminiature; Length: 1 m; Conductor cross-section: 0.25 mm²



www.wago.com/706-160_515-100

Item description

Note:

When using more than 10 wires, the maximum current per wire must be reduced to 1 A.

Data

Electrical data

Operating voltage	≤ AC/DC 35 V
Current per wire (max.)	2 A

Connection data

Number of poles	15
Connection type (1)	System
Pole number 1	15
Pluggable connectors	D-sub male connector
Connection type 2	System
Pole number 2	15
Connector 2	Sub-Min-D; female connector
Cable type	LiYCY
Wire cross-section	0.25 mm²
Color code	per DIN VDE 47100

Physical data

Oalala lawath	4
Cable length	1 m

Material data

Maight	170 ~
Weight	179 g

Environmental requirements

|--|

Subject to changes. Please also observe the further product documentation!

WAGO Corporation Do you have any questions about our products?

Germantown, WI 53022 We are always happy to take your call at +49 (571) 887-44222.

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

Data sheet | Item number: 706-160/515-100

www.wago.com/706-160_515-100



Commercial data

PU (SPU)	1 Stück
Packaging type	bag
Country of origin	FR
GTIN	4055143976886
Customs tariff number	8544429090

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 706-160/515-100

URL Download

Connection cable; 15-pole; with solder pin; Male and female connector; 15-pole; D-subminiature; Length: 1 m; Conductor cross-section: 0.25 mm²

Installation Notes

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO Corporation Germantown, WI 53022 Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us