
Standard Line; 7.0" (17.8 cm); 800 x 480 pixels; 2 x ETHERNET, 2 x USB,


Audio; Visu Panel

www.wago.com/762-4203_8000-001









Item description

PIO2 hardware configuration

- 2 x ETHERNET port for connecting to field devices and the engineering tool
- 2 x USB port for optional connection of a USB stick, mouse or keyboard
- Audio interface for connecting a headphone or loudspeaker

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

www.wago.com/762-4203_8000-001



Data

Technical Data

Display diagonal	7 inches (17.8 cm)
Display	Resistive touchscreen
Display colors	16 million colors
Graphics resolution	(800 x 480) px
Visualization	Webserver
	Web Visu
ETHERNET protocols	DHCP
	DNS
	FTP
	FTPS
	HTTP
	HTTPS
	SSH
Communication	EtherNet/IP TM Adapter (Slave), library for e!RUNTIME (prerequisite: e!
	RUNTIME PLC 600 license)
	Modbus TCP Master/Slave (prerequisite: e!RUNTIME PLC 600
	license)
	EtherCAT Master, requires an additional license and an existing e!
	RUNTIME PLC 600 license on the device
Operating system	Real-time Linux (with RT-Preempt patch)
Processor	ARM [®] Cortex™ A9
Programming environment	e!COCKPIT (based on CODESYS V3)
Main memory (RAM)	2,048 MB
Internal memory (flash)	4096 MB
Program memory	32 MB
Data memory	128 MB
Memory card type	microSD (max. 2 GB); microSDHC (max. 32 GB)
Indicators	five LEDs
Controls	Resistive touch panel, two capacitive keys, proximity sensor
Supply voltage	SELV DC 24 V (18 31.2 V); with reverse voltage protection

Connection data

Connection technology: communication/fieldbus	Modbus TCP: 2 x RJ-45; 2 x USB 2.0 host (type A)

Subject to changes. Please also observe the further product documentation!

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

www.wago.com/762-4203_8000-001



Physical data

Width	213 mm / 8.386 inch
Height	167 mm / 6.575 inch
Depth	58 mm / 2.283 inch
Panel cutout (W x H)	(198 x 152) mm

Mechanical data

Weight	982 g
Front panel	Polyester film

Environmental Requirements

Surrounding air temperature (operation)	-20 55 °C (in vertikaler Einbaulage; -20 +50 °C, abweichende Einbaulagen)
Surrounding air temperature (storage)	-20 80 °C
Protection type	IP65
Note on protection type	IP65 (front side); IP20 (rear side), per EN 60529
Relative humidity (without condensation)	90 %
Mounting type	Clamping elements (included) or VESA mount (4 x M4x8)

Commercial data

Packaging type	BOX
Country of origin	DE
GTIN	4055143839396
Customs tariff number	84714100000

Approvals / Certificates

Country specific Approvals

			Certificate
Logo	Approval	Additional Approval Text	name
	KC	Article 58-2, Clause 3	MSIP-
	National Radio Research Agency		REM-W43-
			WBP762

Ship Approvals

Certificate

Subject to changes. Please also observe the further product documentation!

WAGO Corporation Germantown, WI 53022 Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

www.wago.com/762-4203_8000-001



E175199

Logo Approval Additional Approval Text name **DNV GL** TAA00001FS

Det Norske Veritas, Germanischer Lloyd

UL-Approvals

Certificate Logo Approval Additional Approval Text name

> UL UL 61010-2-201

Underwriters Laboratories Inc. (ORDINARY LOCATIONS)

Counterpart

Compatible products

software

Item no.: 2759-208/210-1000 www.wago.com/2759-208 /210-1000 Library MTP; Single License

Item no.: 2759-208/211-1000 www.wago.com/2759-208

/211-1000 Library MTP; Single License; Online activation

Item no.: 2759-216/210-1000 www.wago.com/2759-216

/210-1000 e!RUNTIME; IEC 61131 runtime environment; 600; Single License

Item no.: 2759-266/210-1000 www.wago.com/2759-266

e!RUNTIME; EtherCAT Master; 600; Single License /210-1000

assembling

Item no.: 762-9001 www.wago.com/762-9001

Clamping elements (4 pieces)

Downloads Documentation

Manual

Subject to changes. Please also observe the further product documentation!

WAGO Corporation Do you have any questions about our products? Germantown, WI 53022 We are always happy to take your call at {0}. Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

www.wago.com/762-4203_8000-001



WAGO Touch Panel 600	1.4.0 Aug 21, 2020	pdf 2.6 MB	Download
Standard Line			
Bid Text			
762-4203/8000-001	Feb 19, 2019	xml	Download
X81 - Datei		5.9 kB	
762-4203/8000-001	Jan 4, 2019	docx	Download
docx - Datei		22.5 kB	
Tutorial			
Establish connection to a controller using SSH	1.0	mp4	Download
In this video we are demonstrating how to establish a SSH connec-tion with a	Aug 5, 2017	29.0 MB	
controller using for example PuTTY to be able to work with the LINUX console. Contents: 0:21 Download and install the SSH client; 0:40 Establish the SSH			
connection; 0:50 Log on to the Controller			
System Description			
Touch Panel 600, system description		pdf 727.2 kB	Download
Engineering-Software			
e!COCKPIT			
e!COCKPIT	V 1.7.0.5	ZIP	Download
Register at no cost and test our engineering software for 30 days.	Jul 1, 2020	2.8 GB	
Runtime Software			
Firmware			
Firmware: 762-4203/8000-001 Touch Panel 600; 17.8 cm (7.0"); 800 x 480 pixels; 2 x ETHERNET, 2 x USB, Audio; Visu Panel	17 Jul 20, 2020	zip 151.8 MB	Download

Installation Notes

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

www.wago.com/762-4203_8000-001



Product family

Touch Panel 600 Show all products from the family

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us