

Data sheet | Item number: 770-631/350-000

Distribution box; Distribution; Three-phase to single-phase (400 V / 230 V); 2 circuits; 1 input; 3 outputs; Coding A + P

www.wago.com/770-631_350-000



Data

Electrical data

Note on contact resistance	approx. 1 m Ω contact resistance approx. 0.25 m Ω contact transition plug/socket
----------------------------	--

IEC Approvals

Legend (ratings)	(III / 3) \triangleq Overvoltage category III / Pollution degree 3
------------------	--

Ratings per UL

Rated voltage (UL 1977)	600 V
Rated current UL 1977	23 A

Physical data

Width	190 mm / 7.48 inch
Height	30 mm / 1.181 inch

Mechanical data

Mounting type	Wall screw adapter Secured to mounting plate
---------------	---

Plug-in connection

Mismating protection	Yes
Locking of plug-in connection	locking lever

Material data

Insulation material	Polyamide 66 (PA 66)
Contact material	Copper or copper alloy, surface-treated
Fire load	61.965 MJ
Weight	381.7 g

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.




Environmental requirements

Processing temperature	-5 ... +40 °C
Continuous operating temperature	-35 ... +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

PU (SPU)	1 Stück
Country of origin VKOrg Germany	DE
GTIN	4050821302902
Customs tariff number VKOrg Germany	85366990990

Installation Notes



Securing the mounting plate with WINSTA®
Distribution Box to the wall (e.g., via stud gun).

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.