Data sheet | Item number: 771-8982/105-601 pre-assembled connecting cable; Eca; Socket/open-ended; 2-pole; Cod. I; H05VV-F 2 x 1.0 mm²; 6 m



www.wago.com/771-8982_105-601



Item description

- Protected against mismating and maintenance-free
- Push-in CAGE CLAMP® spring pressure connection technology allows solid conductors to be simply pushed into a unit
- Two-wire connection per pole for loops or bridges

Note:

Cables with different fire load are available in the eShop

Safety information 1:

Application note for the U.S. market (USR): Some versions may also be used for current interruption in accordance with the UL certificate in select applications with currents below 16 A and voltages up to 600 V. For further information, please contact your local sales office.

Data Connection data

Connection 1

Wire cross-section

1 mm²

Required accessories

Locking levers

Locking lever; for flying leads; for manual operation; black	www.wago.com/770-101
ltem no.: 770-111	www.wago.com/770-111
Locking lever; for flying leads; for tool operation; black	
Item no.: 770-121	www.wago.com/770-121
Locking lever; for flying leads; for manual operation; white	
ltem no.: 770-131	
	www.wago.com/770-131
-	Locking lever; for flying leads; for tool operation; black Item no.: 770-121 Locking lever; for flying leads; for manual operation; white

WAGO Corporation Germantown, WI 53022 Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222 Email: info.us@wago.com | Web: www.wago.us Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.



Locking lever; for flying leads; for tool operation; white

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Corporation Germantown, WI 53022 Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222 Email: info.us@wago.com | Web: www.wago.us Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.