



Data
Mechanical data

Mounting type	Front installation
---------------	--------------------

Environmental requirements

Surrounding air temperature (operation)	-20 °C ... +70 °C
Surrounding air temperature (storage)	-20 °C ... +80 °C
Pollution degree (5)	3

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at {0}.



Technical data

Bit transfer	10 Gbit/s
Rated voltage	50 V
Rated current	1.5 A
Service life	>750 insertion cycles

Material data

Flammability class per UL94	V0
Contact material	CuSn, gold-plated
Housing material	PA, PBT
Weight	23.8 g
Shield	Connected through

Physical data

Depth	70 mm
-------	-------

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 8000-099/000-1764	URL	Download
--	-----	----------

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at {0}.