



Data  
Electrical data

IEC Approvals

Rated voltage (III / 3)	1000 V
Rated current	125 A

Subject to changes. Please also observe the further product documentation!

WAGO Corporation  
Germantown, WI 53022  
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222  
Email: [info.us@wago.com](mailto:info.us@wago.com) | Web: [www.wago.us](http://www.wago.us)

Do you have any questions about our products?  
We are always happy to take your call at {0}.



Rated current 2	150 A
-----------------	-------

## Physical data

Width	26.5 mm / 1.043 inch
Depth	6.2 mm / 0.244 inch

## Material data

Color	yellow
Insulation material	Polyamide (PA66)
Flammability class per UL94	V2
Weight	14.1 g

## Environmental requirements

Continuous operating temperature	-35 ... +105 °C
----------------------------------	-----------------

## Commercial data

Packaging type	bag
Country of origin	DE
GTIN	4055143940917
Customs tariff number	8536698000

## Downloads

### Documentation

#### Bid Text

883-3542	xml	Download
X81 - Datei	2.9 kB	

883-3542	docx	Download
docx - Datei	12.6 kB	

#### Additional Information

Technical explanations	2019 Apr 3	pdf	Download
		2.2 MB	

## Environmental Product Compliance

### Compliance Search

Subject to changes. Please also observe the further product documentation!

WAGO Corporation  
 Germantown, WI 53022  
 Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222  
 Email: [info.us@wago.com](mailto:info.us@wago.com) | Web: [www.wago.us](http://www.wago.us)

Do you have any questions about our products?  
 We are always happy to take your call at {0}.

Environmental Product Compliance 883-3542

Jumper; 2-way; insulated; yellow

---

## Installation Notes



Subject to changes. Please also observe the further product documentation!

---

WAGO Corporation  
Germantown, WI 53022  
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222  
Email: [info.us@wago.com](mailto:info.us@wago.com) | Web: [www.wago.us](http://www.wago.us)

Do you have any questions about our products?  
We are always happy to take your call at {0}.