Data sheet | Item number: 890-524

Shield connecting plate; 4-pole; for sockets

www.wago.com/890-524



Item description

Shield termination WINSTA® MINI 4-pole

Choose tried-and-tested accuracy for the electrical installation in your project: The shield termination from the *WINSTA*® MINI product line. You can rely on the quality of WINSTA® components from WAGO for your electrical installation accessories too.

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

Data sheet | Item number: 890-524

www.wago.com/890-524



Particularly where space is tight, our smallest pluggable connection system, WINSTA® MINI, conveniently displays its advantageous properties. It saves space, and, with Push-in CAGE CLAMP® spring pressure connection technology, it additionally can be installed quickly, since the connection is low-maintenance and can be performed without screw connections.

Lower costs through fast commissioning and elimination of service expenses – solutions from WINSTA® MINI

The WINSTA® Pluggable Connection System is perfectly tailored to the strict requirements of building installation. It makes electrical installation pluggable, and therefore more efficient, even more reliable, and error-free. Use of this pre-assembled system decreases assembly times and installation errors at the construction site. Now you can also reduce installation expenses without compromising quality and safety: The WINSTA® MINI accessory eliminates the need for servicing and prevents unnecessary downtime.

- easy tool-free operation, a wide range of coding options
- fast, secure installation

Data

Connection data

Connection 1

Number of poles 4	
-------------------	--

Mechanical data

Suitable	for socket

Material data

Weight	1.8 g
Material	SE Cu; special tinned

Environmental requirements

Processing temperature	-5 +40 °C
Continuous operating temperature	-35 +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

PU (SPU)	50 (1) Stück
Packaging type	box

Subject to changes. Please also observe the further product documentation!

WAGO Corporation Do you have any questions about our products?

Germantown, WI 53022 We are always happy to take your call at +49 (571) 887-44222.

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

Data sheet | Item number: 890-524

www.wago.com/890-524



Country of origin	DE
GTIN	4055143820394
Customs tariff number	85366990990

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 890-524 URL Download Shield connecting plate; 4-pole; for sockets

Installation Notes

Product family

WINSTA® MINI

Show all products from the family

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.