

Data sheet | Item number: 891-8993/005-207

pre-assembled interconnecting cable; Socket/plug; 3-pole; Cod. B; 2 m; 1,00 mm²; pink

www.wago.com/891-8993_005-207



Item description

Cable assembly *WINSTA*® MINI B coding

The *WINSTA*® MINI cable assembly with protection type IP20 is the pluggable solution for your use in control cabinets, on PCBs or for lighting connections. On PCBs, in control cabinets or for connecting lights – pluggable installation connectors from WAGO allow you to establish connections according to many different requirements in no time flat. For greater protection in electrical installations, the pluggable installation connector is provided with mechanical protection against mismating. Solutions like the *WINSTA*® MINI pluggable installation connectors with B coding are suitable for applications related to process control, such as for lighting or within data networks. Due to its particularly small dimensions, our *WINSTA*® MINI Pluggable Connection System with Push-in CAGE CLAMP® spring pressure connection technology is specifically suitable in very tight spaces, i.e., for installations when very little room is available. This product meets all the mandatory fire protection requirements of fire class E; therefore it can be used in areas where fire safety is relevant.

Pluggable connections instead of screw connections – cable assemblies from WAGO

A socket and a plug are available. *WINSTA*® is the pluggable connection system that is optimally tailored to the strict requirements of electrical installation. It allows fast, secure and, above all, error-free installation of components and cables. Choose durability and quality – the *WINSTA*® MINI pluggable installation connector with protection type IP20 from WAGO makes the electrical installation of electrical components visibly easier.

- protection against mismating eliminates errors
- compact design for conductors with a cross-section up to 1.5 mm²
- for automation controllers
- ready for immediate use
- quick replacement of defective units during ongoing operation

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Data Notes

| | |
|------|---|
| Note | Cables with a different fire class can be found in the eShop. |
|------|---|

| | |
|-----------|---|
| Variants: | Other pole markings Other versions (or variants) can be requested from WAGO Sales or configured at https://configurator.wago.com/ . |
|-----------|---|

Electrical data

| | |
|----------------------------|--|
| Note on contact resistance | approx. 1 mΩ of contact resistance approx. 0.25 mΩ contact transition plug/socket |
|----------------------------|--|

IEC Approvals

| | |
|-------------------------------|---|
| Ratings per | IEC/EN 60664-1 |
| Rated voltage (III / 3) | 250 V |
| Rated impulse voltage (III/3) | 4 kV |
| Rated current | 10 A |
| Legend (ratings) | (III / 3) ≙ Overvoltage category III / Pollution degree 3 |

Ratings per UL

| | |
|------------------------|---|
| Note for the US market | Some versions may also be used for current interruption in accordance with the UL certificate in select applications with currents below 5 A and voltages up to 600 V. For further information, please contact your local sales office. |
|------------------------|---|

Connection data

| | |
|----------------------------|---------------------------|
| Total number of potentials | 3 |
| Conductor preparation | ultrasonically tip-bonded |

Connection 1

| | |
|-------------------------|-------------------|
| Number of poles | 3 |
| Sheathed cable diameter | 6.3 ... 8 mm |
| Wire cross-section | 1 mm ² |
| Connection type | Socket - Plug |

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Physical data

| | |
|--------------|---------------------|
| Pin spacing | 4.4 mm / 0.173 inch |
| Total length | 2 m |

Mechanical data

| | |
|---|---|
| Application | Control technology |
| Coding | B |
| Variable coding | No |
| Marking | 1 2 3 |
| Potential Marking | 1 2 3 |
| Mating force of a plug-in connection | approx. 20 ... 70 N (depending on pole number) |
| Retention force of a plug-in connection | when locked: > 80N |
| Unmating force of a plug-in connection | when unlocked: approx. 20 ... 70 N (depending on pole number) |
| Number of mating cycles | 200, without resistive load |
| Connection type | Socket - Plug |
| Type of pre-assembled cable | Interconnecting cable |
| Cable type | Control line 3 x 1 |
| Protection type | IP20; IP40 when mated |

Plug-in connection

| | |
|-------------------------------|---|
| Mismating protection | Yes |
| Note on mismating protection | All WINSTA® components are 100% protected against mismating when: a.) plugging different numbers of poles b.) plugging while rotated 180 c.) plugging while laterally staggered d.) plugging one pole |
| Locking lever | Can be retrofitted |
| Locking of plug-in connection | locking lever |

Material data

| | |
|-------------------------|--|
| Note (material data) | Information on material data can be found here |
| Color | pink |
| Insulation material | Polyamide (PA66) |
| Fire class per EN 50575 | E _{ca} |
| Contact material | Copper or copper alloy; surface-treated |

Subject to changes. Please also observe the further product documentation!



| | |
|----------------------------------|------------|
| Fire load | 0.11 MJ |
| Connector color | pink |
| Printing color of mating face | black |
| Strain relief color | black |
| Sheathed cable color | gray |
| Printing color of sheathed cable | black |
| Halogen-free | No |
| Sheath material | PVC |
| Weight | 158.7 g |
| Copper weight of the pipe | 0.029 kg/m |

Environmental requirements

| | |
|--|---|
| Processing temperature | -5 ... +40 °C |
| Continuous operating temperature | -35 ... +85 °C |
| Note on continuous operating temperature | PVC cable for temperatures ≤ 70 °C (including halogen-free) Insulating parts for temperatures ≤ 105 °C |

Commercial data

| | |
|-------------------------------------|---------------|
| PU (SPU) | 1 Stück |
| Packaging type | unpacked |
| Country of origin VKOrg Germany | PL |
| GTIN | 4055143514460 |
| Customs tariff number VKOrg Germany | 85444290900 |

Required accessories

Locking levers

| | |
|--|--|
| Locking system | |
| Item no.: 890-111 Locking lever; for flying leads; for tool operation; black | www.wago.com/890-111 |
| Item no.: 890-101 Locking lever; for manual operation; black | www.wago.com/890-101 |
| Item no.: 890-121 Locking lever; for manual operation; white | www.wago.com/890-121 |
| Item no.: 890-131 Locking lever; for flying leads; for tool operation; white | www.wago.com/890-131 |

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Optional accessories

Cover

Other



Item no.: 897-2001

Protective cap; Type1; for sockets and plugs; PVC; red

www.wago.com/897-2001

Mounting

Mounting accessories

Item no.: 890-310

Mounting carrier; 2- to 5-pole; for flying leads; black

www.wago.com/890-310

Item no.: 890-311

Mounting carrier; 2- to 5-pole; for flying leads; white

www.wago.com/890-311

Downloads

Documentation

Bid Text

| | | | |
|---------------------------------|-------------|----------------|----------|
| 891-8993/005-207 X81 - Datei | 2019 Feb 19 | xml 3.0 kB | Download |
| 891-8993/005-207 doc - Datei | 2015 Jun 2 | doc 24.6 kB | Download |

Environmental Product Compliance

Compliance Search

| | | |
|---|-----|----------|
| Environmental Product Compliance 891-8993/005-207 pre-assembled interconnecting cable; Socket/plug; 3-pole; Cod. B; 2 m; 1,00 mm ² ; pink | URL | Download |
|---|-----|----------|

Installation Notes

Product family

WINSTA® MINI

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO Corporation
Germantown, WI 53022
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222
Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.