

## Data sheet | Item number: 891-8993/006-503

pre-assembled interconnecting cable; Eca; Socket/plug; 3-pole; Cod. B; 5 m;  
1,50 mm<sup>2</sup>; gray

[www.wago.com/891-8993\\_006-503](http://www.wago.com/891-8993_006-503)



### Item description

#### Cable assembly **WINSTA®** MINI with protection against mismating

The **WINSTA®** MINI cable assembly B coding supports fast, reliable installation. WAGO pluggable installation connectors are useful when criteria repeat or are distributed on a specific grid, for example for installing grid lighting or flush-mount lighting. The color coding and mechanical coding of the pluggable installation connector ensure error-free installation of the individual components – including protection against mismating. B coding enables the **WINSTA®** MINI pluggable installation connectors to be used for application control in automation, robotics, and mechanical engineering. **WINSTA®** MINI follows the trend towards miniaturisation. Our smallest pluggable connection system is especially suitable for lights, for instance, since due to LED technology, these offer significantly less space for the connection technology. According to the European CPR, the fire class of the cables used in construction is critical for building safety, too. For buildings with average safety requirements, cable assemblies with fire class E are suitable.

#### Fast, secure pluggable connections – cable assemblies from WAGO

The cable is pre-assembled with a socket and a plug. The **WINSTA®** Pluggable Connection System is ideally tailored to the very strict requirements of building installation. It makes electrical installation pluggable, and therefore faster, more reliable, and error-free. Using this pre-assembled system reduces time spent on assembly and errors during installation at the construction site. Now you can also lower installation expenses without compromising quality and safety: The **WINSTA®** MINI pluggable installation connector with strain relief hosting reduces the need for servicing and prevents unnecessary downtime.

- pluggable installation connectors with protection against mismating
- easy tool-free operation, a wide range of coding options
- with B coding for controllers, for example sun blinds and lighting fixtures
- flexible installation to save space
- quick replacement of defective units during ongoing operation

Subject to changes. Please also observe the further product documentation!

WAGO Corporation  
Germantown, WI 53022  
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222  
Email: [info.us@wago.com](mailto:info.us@wago.com) | Web: [www.wago.us](http://www.wago.us)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Data Notes

|      |   |
|------|---|
| Note | Cables with a different fire class can be found in the eShop. |
|------|---|

|           |   |
|-----------|---|
| Variants: | Other pole markings<br>Other versions (or variants) can be requested from WAGO Sales or configured at <a href="https://configurator.wago.com/">https://configurator.wago.com/</a> . |
|-----------|---|

## Electrical data

|                            |  |
|----------------------------|--|
| Note on contact resistance | approx. 1 mΩ of contact resistance<br>approx. 0.25 mΩ contact transition plug/socket |
|----------------------------|--|

## IEC Approvals

|                               |   |
|-------------------------------|---|
| Ratings per                   | IEC/EN 60664-1  |
| Rated voltage (III / 3)       | 250 V   |
| Rated impulse voltage (III/3) | 4 kV  |
| Rated current                 | 16 A  |
| Note (rated current)          | 13 A for 3-pole load                                      |
| Legend (ratings)              | (III / 3) ≙ Overvoltage category III / Pollution degree 3 |

## Ratings per UL

|                        |   |
|------------------------|---|
| Note for the US market | Some versions may also be used for current interruption in accordance with the UL certificate in select applications with currents below 5 A and voltages up to 600 V. For further information, please contact your local sales office. |
|------------------------|---|

## Connection data

|                            |                           |
|----------------------------|---------------------------|
| Total number of potentials | 3                         |
| Conductor preparation      | ultrasonically tip-bonded |

## Connection 1

|                         |                |
|-------------------------|----------------|
| Number of poles         | 3              |
| Sheathed cable diameter | 7.4 ... 9.4 mm |
| Wire cross-section      | 1.5 mm²        |
| Connection type         | Socket - Plug  |

Subject to changes. Please also observe the further product documentation!

WAGO Corporation  
Germantown, WI 53022  
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222  
Email: [info.us@wago.com](mailto:info.us@wago.com) | Web: [www.wago.us](http://www.wago.us)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## Physical data

|              |                     |
|--------------|---------------------|
| Pin spacing  | 4.4 mm / 0.173 inch |
| Total length | 5 m                 |

## Mechanical data

|   |   |
|---|---|
| Application                             | Control technology  |
| Coding                                  | B   |
| Variable coding                         | No  |
| Marking                                 | 1 2 3   |
| Potential Marking                       | 1 2 3   |
| Mating force of a plug-in connection    | approx. 20 ... 70 N (depending on pole number)                |
| Retention force of a plug-in connection | when locked: > 80N  |
| Unmating force of a plug-in connection  | when unlocked: approx. 20 ... 70 N (depending on pole number) |
| Number of mating cycles                 | 200, without resistive load                                   |
| Connection type                         | Socket - Plug   |
| Type of pre-assembled cable             | Interconnecting cable   |
| Cable type                              | Control line 3 x 1.5  |
| Protection type                         | IP20; IP40 when mated   |

## Plug-in connection

|                               |   |
|-------------------------------|---|
| Mismating protection          | Yes   |
| Note on mismating protection  | All WINSTA® components are 100% protected against mismating when:<br>a.) plugging different numbers of poles<br>b.) plugging while rotated 180<br>c.) plugging while laterally staggered<br>d.) plugging one pole |
| Locking lever                 | Can be retrofitted  |
| Locking of plug-in connection | locking lever   |

## Material data

|                         |  |
|-------------------------|--|
| Note (material data)    | Information on material data can be found here |
| Color                   | gray   |
| Insulation material     | Polyamide (PA66)                               |
| Fire class per EN 50575 | E <sub>ca</sub>                                |
| Contact material        | Copper or copper alloy; surface-treated        |
| Fire load               | 0.168 MJ                                       |

Subject to changes. Please also observe the further product documentation!



|                                  |            |
|----------------------------------|------------|
| Connector color                  | gray       |
| Printing color of mating face    | black      |
| Strain relief color              | black      |
| Sheathed cable color             | gray       |
| Printing color of sheathed cable | black      |
| Halogen-free                     | No         |
| Sheath material                  | PVC        |
| Weight                           | 507.4 g    |
| Copper weight of the pipe        | 0.043 kg/m |

## Environmental requirements

|  |   |
|--|---|
| Processing temperature                   | -5 ... +40 °C   |
| Continuous operating temperature         | -35 ... +85 °C  |
| Note on continuous operating temperature | PVC cable for temperatures ≤ 70 °C (including halogen-free)<br>Insulating parts for temperatures ≤ 105 °C |

## Commercial data

|                                     |               |
|-------------------------------------|---------------|
| PU (SPU)                            | 1 Stück       |
| Packaging type                      | unpacked      |
| Country of origin VKOrg Germany     | PL            |
| GTIN                                | 4050821446514 |
| Customs tariff number VKOrg Germany | 85444290900   |

## Required accessories

### Locking levers

|   |  |
|---|--|
| Locking system  |  |
| Item no.: 890-111<br>Locking lever; for flying leads; for tool operation; black | <a href="http://www.wago.com/890-111">www.wago.com/890-111</a> |
| Item no.: 890-101<br>Locking lever; for manual operation; black                 | <a href="http://www.wago.com/890-101">www.wago.com/890-101</a> |
| Item no.: 890-121<br>Locking lever; for manual operation; white                 | <a href="http://www.wago.com/890-121">www.wago.com/890-121</a> |
| Item no.: 890-131<br>Locking lever; for flying leads; for tool operation; white | <a href="http://www.wago.com/890-131">www.wago.com/890-131</a> |

## Optional accessories

### Cover

Subject to changes. Please also observe the further product documentation!

WAGO Corporation  
Germantown, WI 53022  
Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222  
Email: [info.us@wago.com](mailto:info.us@wago.com) | Web: [www.wago.us](http://www.wago.us)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



Other

**Item no.: 897-2001**

Protective cap; Type1; for sockets and plugs; PVC; red

[www.wago.com/897-2001](http://www.wago.com/897-2001)**Mounting**

## Mounting accessories

**Item no.: 890-310**

Mounting carrier; 2- to 5-pole; for flying leads; black

[www.wago.com/890-310](http://www.wago.com/890-310)**Item no.: 890-311**

Mounting carrier; 2- to 5-pole; for flying leads; white

[www.wago.com/890-311](http://www.wago.com/890-311)**Downloads****Documentation****Bid Text**

| Item no.         | Date        | File name   | Size   | Download                 |
|------------------|-------------|-------------|--------|--------------------------|
| 891-8993/006-503 | 2019 Feb 19 | X81 - Datei | 3.0 kB | <a href="#">Download</a> |

|                  |            |             |         |                          |
|------------------|------------|-------------|---------|--------------------------|
| 891-8993/006-503 | 2015 Jun 2 | doc - Datei | 24.6 kB | <a href="#">Download</a> |
|------------------|------------|-------------|---------|--------------------------|

**Environmental Product Compliance****Compliance Search**

| Item no.         | Date       | File name   | Size    | Download                 |
|------------------|------------|-------------|---------|--------------------------|
| 891-8993/006-503 | 2015 Jun 2 | doc - Datei | 24.6 kB | <a href="#">Download</a> |

**Installation Notes****Product family****WINSTA® MINI**[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO Corporation  
 Germantown, WI 53022  
 Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222  
 Email: [info.us@wago.com](mailto:info.us@wago.com) | Web: [www.wago.us](http://www.wago.us)

Do you have any questions about our products?  
 We are always happy to take your call at +49 (571) 887-44222.