

Distribution box; Single-phase current (230 V); 1 input; 13 outputs; Cod. A;

MIDI; black

www.wago.com/899-631\_334-000







## Item description

## WINSTA® Boxen rated current 25 A

The distribution box from the WINSTA® Boxen product line with a current rating of 25 A guarantees you the greatest possible flexibility in electrical installation. With WAGO, you can enjoy the advantages of a large selection of expansions for the WINSTA® product line. The mechanical coding and color coding of the distribution box ensure error-free installation of the individual components – including protection against mismating. The

Subject to changes. Please also observe the further product documentation!

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/899-631\_334-000



distribution box offers protection against contact with live components in accordance with protection type IP20 (When mated: IP2xC (These compact connectors are not designed for use in open, easily accessible areas!)). Standard mains applications for almost any domain of use can be realised with WINSTA® Boxen with A coding. This distribution box is used for electrical currents up to 25 A. Thus the product is especially suitable for high power loads.

# Push-in CAGE CLAMP® spring pressure connection technology – pluggable installation instead of laborious screw connections!

The WINSTA® Pluggable Connection System is ideally tailored to the very strict requirements of building installation. It makes electrical installation pluggable, and therefore more efficient, even more reliable, and error-free. Use of this pre-assembled system reduces assembly times and installation errors at the construction site. Choose quality and durability – the WINSTA® Boxen with protection against mismating from WAGO make the installation of electrical components visibly easier.

- protection against mismating eliminates errors
- clear slot identification for easy commissioning
- cost savings reduction of on-site waste
- suitable for any application
- convenient installation and commissioning

## Data

### Electrical data

Note on contact resistance	approx. 1 m $\Omega$ contact resistance
	approx. $0.25 \text{ m}\Omega$ contact transition (plug/socket)

#### **IEC Approvals**

Ratings per	IEC/EN 60664-1
Rated voltage (III / 3)	250 V
Rated impulse voltage (III/3)	4 kV
Rated current	25 A
Legend (ratings)	(III / 3) ≙ Overvoltage category III / Pollution degree 3

### Physical data

Width	190 mm / 7.48 inch
Height	30 mm / 1.181 inch
Depth	145 mm / 5.709 inch

Subject to changes. Please also observe the further product documentation!

WAGO Corporation Germantown, WI 53022 Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

Email: info.us@wago.com | Web: www.wago.us

www.wago.com/899-631\_334-000



### Mechanical data

Internal wiring	4 mm <sup>2</sup>		
Application	General mains applications		
Coding	A		
Mounting type	Wall, screw mount Installation on mounting plate		
Protection type	IP20; When mated: IP2xC (These compact connectors are not designed for use in open, easily accessible areas!)		

## Plug-in connection

Mismating protection	Yes
Note on mismating protection	All WINSTA® components are 100% protected against mismating when: a.) plugging different numbers of poles b.) plugging while rotated 180 c.) plugging while laterally staggered d.) plugging one pole
Locking of plug-in connection	locking lever

## Material data

Note (material data)	Information on material data can be found here
Color	black
Insulation material	Polyamide (PA66)
Contact material	Copper or copper alloy; surface-treated
Fire load	79.585 MJ
Weight	466.5 g

## **Environmental requirements**

Processing temperature	-5 +40 °C
Continuous operating temperature	-35 +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

## Commercial data

PU (SPU)	1 Stück
Packaging type	box
Country of origin VKOrg Germany	DE
GTIN	4055143303279
Customs tariff number VKOrg Germany	85366990990

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$ 

WAGO Corporation
Germantown, WI 53022
Phone: 1, 200 DIN PAUL (246, 7245) February (262) 255

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/899-631\_334-000



## Counterpart

Item no.770-103
Socket; with strain relief housing; 3-pole; Cod. A; 4,00 mm²; black

Item no.770-113
Plug; with strain relief housing; 3-pole; 4,00 mm²; black

Item no.770-203
Socket; 3-pole; Cod. A; 4,00 mm²; black

Item no.770-203/035-000
Socket; with strain relief housing; 3-pole; Cod. A; 4,00 mm²; black

Item no.770-213/035-000
Socket; with strain relief housing; 3-pole; Cod. A; 4,00 mm²; black

Item no.770-213/035-000

Www.wago.com/770-213/035-000

Www.wago.com/770-213/035-000

## Optional accessories

Item no.770-213

Plug; 3-pole; 4,00 mm<sup>2</sup>; black

### Mounting

Mounting accessories

Item no.: 770-680

Mounting plate; for distribution boxes

www.wago.com/770-680

# Downloads Documentation

#### **Bid Text**

 899-631/334-000
 2019 Feb 19
 xml
 Download

 899-631/334-000
 2015 Mar 11
 doc Download
 Download

 ausschreiben.de 899-631/334-000
 URL
 Download

Subject to changes. Please also observe the further product documentation!

Plug; with strain relief housing; 3-pole; 4,00 mm<sup>2</sup>; black

WAGO Corporation Germantown, WI 53022 Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222 Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

www.wago.com/770-213

Email: info.us@wago.com | Web: www.wago.us

www.wago.com/899-631\_334-000



# **Environmental Product Compliance**

Compliance Search

Environmental Product Compliance 899-631/334-000 URL Download

Distribution box; Single-phase current (230 V); 1 input; 13 outputs; Cod. A; MIDI; black

Insta	llation	Note	s		
Instal	lation				

Securing the mounting plate with WINSTA Distribution Box to the wall (e.g., via stud gun).

## **Product family**

### WINSTA® boxes

WINSTA® ist das Steckverbindersystem, das optimal auf die hohen Anforderungen in der Gebäudeinstallation zugeschnitten ist. Es macht die Elektroinstallation steckbar und dadurch schnell, sicher und fehlerfrei. Dies gilt auch in weiteren Anwendungen wie z. B. im Schiffbau, in der Bahntechnik oder in der Industrie.

Show all products from the family

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$ 

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.