

Data sheet | Item number: 899-631/386-000

Distribution box; Series switching; 1 input; 7 outputs; Cod. A, S; MIDI; black

www.wago.com/899-631_386-000







Item description

WINSTA® Boxen rated current 25 A

Implement the electrical installation with ease: The distribution box from the WINSTA® Boxen product line with protection against mismating is the product of your choice for error-free electrical installation. You can rely on the level of quality of WINSTA® components from WAGO for your electrical installation accessories too. For greater protection in electrical installations, the distribution box is provided with mechanical protection

Subject to changes. Please also observe the further product documentation!

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

Data sheet | Item number: 899-631/386-000

www.wago.com/899-631_386-000



against mismating. The distribution box is protected in accordance with protection type IP20 (When mated: IP2xC (These compact connectors are not designed for use in open, easily accessible areas!)). This means that users' fingers will never come into contact with energised contact elements. Thanks to the color coding and mechanical A coding of WINSTA® Boxen, you can clearly distinguish different circuits. The rated current and voltage are important criteria for selecting a distribution box: They provide information about possible domains of use and applications. This product has a current rating of 25 A – so it is suitable for powerful loads.

Lower costs through fast commissioning and elimination of service expenses – solutions from WINSTA® Boxen

The WINSTA® Pluggable Connection System allows pluggable electrical installation. This significantly reduces the need for servicing and lowers costs. Choose durability and quality – the WINSTA® Boxen with protection against mismating from WAGO make the installation of electrical components visibly easier.

- protection against mismating eliminates errors
- intuitive distribution box marking
- saves time, since no wiring is required at the construction site
- with A coding for a great number of applications
- quick replacement of defective units during ongoing operation

Data

Electrical data

Note on contact resistance	approx. 1 m Ω contact resistance
	approx. 0.25 m Ω contact transition (plug/socket)

IEC Approvals

Ratings per	IEC/EN 60664-1
Rated voltage (III / 3)	250 V
Rated impulse voltage (III/3)	4 kV
Rated current	25 A
Legend (ratings)	(III / 3) ≙ Overvoltage category III / Pollution degree 3

Physical data

Width	190 mm / 7.48 inch
Height	30 mm / 1.181 inch
Depth	145 mm / 5.709 inch

Subject to changes. Please also observe the further product documentation!

WAGO Corporation

Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us



Mechanical data

Internal wiring	4 mm²
Coding	A
Mounting type	Wall, screw mount Installation on mounting plate
Protection type	IP20; When mated: IP2xC (These compact connectors are not designed for use in open, easily accessible areas!)

Plug-in connection

Mismating protection	Yes
Note on mismating protection	All WINSTA® components are 100% protected against mismating when: a.) plugging different numbers of poles b.) plugging while rotated 180 c.) plugging while laterally staggered d.) plugging one pole
Locking of plug-in connection	locking lever

Material data

Note (material data)	Information on material data can be found here
Color	black
Insulation material	Polyamide (PA66)
Contact material	Copper or copper alloy; surface-treated
Fire load	68.982 MJ
Weight	435 g

Environmental requirements

Processing temperature	-5 +40 °C
Continuous operating temperature	-35 +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

PU (SPU)	1 Stück
Packaging type	box
Country of origin VKOrg Germany	DE
GTIN	4055143305778

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us



Customs tariff number VKOrg Germany

85366990990

Counterpart

3 48	Item no.770-103 Socket; with strain relief housing; 3-pole; Cod. A; 4,00 mm²; black	www.wago.com/770-103
14	Item no.770-113 Plug; with strain relief housing; 3-pole; 4,00 mm²; black	www.wago.com/770-113
	Item no.770-1373 Plug; 3-pole; 4,00 mm²; brown	www.wago.com/770-1373
母學	Item no.770-203 Socket; 3-pole; Cod. A; 4,00 mm²; black	www.wago.com/770-203
100	Item no.770-203/035-000 Socket; with strain relief housing; 3-pole; Cod. A; 4,00 mm²; black	www.wago.com/770-203/035- 000
98	Item no.770-213 Plug; 3-pole; 4,00 mm²; black	www.wago.com/770-213
	Item no.771-9973/006-105 pre-assembled interconnecting cable; Eca; Socket/plug; 3-pole; Cod. S; H05VV-F 3 x 1.5 mm²; 1 m; 1,50 mm²; brown	www.wago.com/771-9973 /006-105

Optional accessories

Mounting

Mounting accessories

Item no.: 770-680

1,50 mm²; brown

Mounting plate; for distribution boxes

Item no.770-213/035-000

Item no.771-9973/206-105

Plug; with strain relief housing; 3-pole; 4,00 mm²; black

www.wago.com/770-680

www.wago.com/770-213/035-

www.wago.com/771-9973

000

/206-105

Downloads

Documentation

Bid Text

899-631/386-000 2019 Feb 19 xml Download 3.4 kB

pre-assembled connecting cable; Eca; Plug/open-ended; 3-pole; Cod. S; H05VV-F 3 x 1.5 mm²; 1 m;

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

Data sheet | Item number: 899-631/386-000

www.wago.com/899-631_386-000



X81 - Datei

899-631/386-000
doc - Datei

Environmental Product Compliance
Compliance Search
Environmental Product Compliance 899-631/386-000

URL Download

Installation Notes

ı	Installation			
ı				
ı				
ı				
ı				
ı				
1				

Securing the mounting plate with WINSTA Distribution Box to the wall (e.g., via stud gun).

Product family

WINSTA® boxes

Distribution box; Series switching; 1 input; 7 outputs; Cod. A, S; MIDI; black

WINSTA® ist das Steckverbindersystem, das optimal auf die hohen Anforderungen in der Gebäudeinstallation zugeschnitten ist. Es macht die Elektroinstallation steckbar und dadurch schnell, sicher und fehlerfrei. Dies gilt auch in weiteren Anwendungen wie z. B. im Schiffbau, in der Bahntechnik oder in der Industrie.

Show all products from the family

Subject to changes. Please also observe the further product documentation!

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us