

Data sheet | Item number: 899-632/102-000

Distribution box; Relay switching; 2 inputs; 1 output; Cod. A, B; MINI, MIDI

www.wago.com/899-632_102-000







Item description

WINSTA® Boxen with protection against mismating

Realize your installation project easily and quickly: The distribution box from the WINSTA® Boxen product line with protection type IP20 is the solution for quick, straightforward installation. With WAGO, you can enjoy the advantages of a large selection of expansions for the WINSTA® product line. For greater protection in electrical installations, the distribution box is provided with mechanical protection against mismating. The

Subject to changes. Please also observe the further product documentation!

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

Data sheet | Item number: 899-632/102-000

www.wago.com/899-632_102-000



distribution box offers touch-proof protection with live components in accordance with protection type IP20 (When mated: IP2xC (These compact connectors are not designed for use in open, easily accessible areas!)).

WINSTA® Boxen solutions for your electrical installation - protected against mismating and maintenance-free

The WINSTA® Pluggable Connection System allows pluggable electrical installation. This significantly reduces the need for servicing and lowers costs. Choose quality and durability – the WINSTA® Boxen with protection against mismating from WAGO make the electrical installation of electrical components significantly easier.

- effective protection against mismating
- intuitive distribution box marking
- products perfectly tailored to your requirements guarantee safe use
- quick replacement of defective units during ongoing operation

Data

Electrical data

Note on contact resistance	approx. 1 m Ω contact resistance		
	approx. 0.25 m Ω contact transition (plug/socket)		
EC Approvals			
Ratings per	IEC/EN 60664-1		
Legend (ratings)	(III / 3) ≙ Overvoltage category III / Pollution degree 3		
Physical data			
Width	190 mm / 7.48 inch		
Height	30 mm / 1.181 inch		
Depth	145 mm / 5.709 inch		
Mechanical data			
Mounting type	Wall, screw mount		
	Installation on mounting plate		
Protection type	IP20; When mated: IP2xC (These compact connectors are not		

Subject to changes. Please also observe the further product documentation!

WAGO Corporation Germantown, WI 53022 Do you have any questions about our products?

designed for use in open, easily accessible areas!)

Germantown, WI 53022

We are always happy to take your call at +49 (571) 887-44222.

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222 Email: info.us@wago.com | Web: www.wago.us



Plug-in connection

Mismating protection	Yes		
Note on mismating protection	All WINSTA® components are 100% protected against mismating		
	when:		
	a.) plugging different numbers of poles		
	b.) plugging while rotated 180		
	c.) plugging while laterally staggered		
	d.) plugging one pole		
Locking of plug-in connection	locking lever		

Material data

Note (material data)	Information on material data can be found here	
Color	black	
Insulation material	Polyamide (PA66)	
Contact material	Copper or copper alloy; surface-treated	
Fire load	6.758 MJ	
Weight	279 g	

Environmental requirements

Processing temperature	-5 +40 °C
Continuous operating temperature	-35 +85 °C
Note on continuous operating temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

PU (SPU)	1 Stück
Packaging type	box
Country of origin VKOrg Germany	DE
GTIN	4055143933391
Customs tariff number VKOrg Germany	8536698000

Counterpart



Item no.770-103
Socket; with strain relief housing; 3-pole; Cod. A; 4,00 mm²; black

www.wago.com/770-103



Item no.770-113

Plug; with strain relief housing; 3-pole; 4,00 mm²; black

www.wago.com/770-113

 $\label{thm:continuity} \textbf{Subject to changes. Please also observe the further product documentation!}$

WAGO Corporation

Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.

Data sheet | Item number: 899-632/102-000

www.wago.com/899-632_102-000





Item no.770-203 Socket; 3-pole; Cod. A; 4,00 mm²; black

www.wago.com/770-203

8

Item no.770-213

Plug; 3-pole; 4,00 mm²; black

www.wago.com/770-213

-186 841-

Item no.891-8992/005-103

pre-assembled interconnecting cable; Eca; Socket/plug; 2-pole; Cod. B; Control cable 2 x 1.0 mm²; 1 m; 1,00 mm²; gray

www.wago.com/891-8992

/005-103

Item no.890-242

Socket; 2-pole; Cod. B; 1,50 mm²; gray

www.wago.com/890-242

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 899-632/102-000

Distribution box; Relay switching; 2 inputs; 1 output; Cod. A, B; MINI, MIDI

URL Download

Installation Notes

Installation		

Securing the mounting plate with WINSTA Distribution Box to the wall (e.g., via stud gun).

Product family

WINSTA® boxes

WINSTA® ist das Steckverbindersystem, das optimal auf die hohen Anforderungen in der Gebäudeinstallation zugeschnitten ist. Es macht die Elektroinstallation steckbar und dadurch schnell, sicher und fehlerfrei. Dies gilt auch in weiteren Anwendungen wie z. B. im Schiffbau, in der Bahntechnik oder in der Industrie.

Show all products from the family

Subject to changes. Please also observe the further product documentation!

WAGO Corporation Germantown, WI 53022

Phone: 1-800-DIN-RAIL (346-7245) | Fax: (262) 255-6222

Email: info.us@wago.com | Web: www.wago.us

Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.