



Description	Item No.	Pack. Unit
"smartPRINTER" Thermal Transfer Printer	258-5000	1
Includes:		
smartSCRIPT Software		
Print roller for marking strips		
Print roller for WMB Inline markers, 5 mm		
Ink ribbon 57 mm x 74 m		
Marking strip	2009-110	1
WMB Inline markers	2009-115	1
Label stand		
Technical Data		
Printing method	Thermal transfer	
Print head	Glass layer, spring-mounted	
Print resolution	300 dpi (12 pixels/mm)	
Print speed	max. 127 mm/s (WAGO recommends 50.8 mm/s)	
Print width (max.)	47 mm	
Print length (max.)	762 mm	
Transmissive or reflective sensor	yes, centrally fixed	
Memory	8 MB Flash, 16 MB SDRAM	
Ink ribbon	External roll diameter: 40 mm; internal core diameter 0.5" (12.7 mm); max. length 110 m; max. width 58 mm	
Interfaces	USB, RS-232, ETHERNET 10/100 Mbps	
Accessories	Label stand, power supply + cable, USB cable, 2 empty cardboard cores, installation poster	
Control panel	Color TFT-LCD display, navigation buttons	
Operating voltage	Automatically adjusts from 100 to 240 A AC, 50-60 Hz	
Length	245 mm	
Height	175 mm	
Width	135 mm	
Weight	2,000 g (without printing material)	
Operating temperature	5 °C to 40 °C (41 °F to 104 °F)	
Storage temperature	-20 °C to 50 °C (-4 °F to 122 °F)	
Certificate	UL	
Selected Accessories		
Ink ribbon K500 for smartPRINTER	258-5005	1
Spare roller for marking strip	258-5006	1
Spare roller for WMB Inline markers	258-5007	1
Marking strip, self-adhesive, 15 mm wide, 50 m roll	210-702	1
Self-adhesive label, 15 x 9 mm, white, 3,000 labels/roll	210-806	1
Self-adhesive label, 20 x 8 mm, yellow, 3,000 labels/roll	210-807/000-002	1
Wire marker for thread-on mounting, (7 x 10.5) mm marking area, 2.5-6 mm² (AWG 14-10) wire cross-section	211-862	1

The terms of delivery and payment of WAGO Kontakttechnik GmbH & Co.KG are applicable.